

Compression dies for Stilo 20, APW 20, HHW 20, MPW 20 and HPW 20



Dies mandrel-shape

for crimping noninsulated terminals DIN 46234, pin-terminals DIN 46230 and connectors DIN 46341 part 1 (page 70-76)

mm ²	art.-no.	mm ²	art.-no.
6	91731	50	91736
10	91732	70	91737
16	91733	95	91738
25	91734	120	91739
35	91735		



Dies

for crimping insulated terminals (page 78-82)

mm ²	art.-no.	mm ²	art.-no.
10	91693	50	91697
16	91694	70	91698
25	91695	95	91699
35	91696		



Dies square-shape

for crimping insulated and noninsulated cord-end-sleeves (page 95-103) crimping width: 22 mm

mm ²	art.-no.	mm ²	art.-no.
6	91705	70	91711
10	91706	95	91712
16	91707	120	91713
25	91708	150	91714
35	91709	185	91715
50	91710	240	91716



Dies for round-forming

for rounding sector-shaped copper and aluminium conductors crimping width: 22 mm

mm ² sm*	mm ² se*	art.-no.
10	—	91718
16	—	91719
25	35	91720
35	50	91721
50	70	91722
70	95	91723
95	120	91724
120	150	91725
150	185	91726
185	240	91727
240	300	91728

*sm = stranded conductors, se = solid conductors