Technical Datasheet Cable Tray System



Turning Bolt

incl. locking nut acc. to DIN EN ISO 10511

RDRS 2

EAN Code: 4013339270002 Smallest packaging unit:20 pcs.









the photorealistic images are to be considered as reference images









Article Description

Turning bolt simply with locking nut acc. to DIN EN ISO 10511, steel, pre-galvanised according to DIN EN 10346, incl. accessories

Incl. accessories

1 FL 6X12-S V, 1 SMS 6 V

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	13 g / pcs.
Weight in kg per 100	1,3 kg/ 100pcs.

Aktualisiert am 28/4/2025 Page 1/3

Technical Datasheet Cable Tray System

RDRS 2

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	15.00 mm
Width	14.00 mm
Depth/length	32.00 mm

Packing Dimension

20 pieces = 1	√ VP1-smallest packaging unit (PU) √ VP1-preferred PU			eferred PU	
Lenght	71.00 mm	Width	70.00 mm	Height	42.00 mm
Gross weight	0,27 kg	Volume	0,000 m³		
Min. quantity	20.00 pcs.	Max. Quantity	20.00 pcs.		

200 pieces = 1 covering box					
Lenght	218 mm	Width	150.00 mm	Height	74.00 mm
Gross weight	2,79 kg	Volume	0,002 m ³		
Min. Quantity	200.00 pcs.	Max. Quantity	200.00 pcs.		

18200 pieces = 1					
Lenght	750 mm	Width	750 mm	Height	730 mm
Gross weight	294 kg	Volume	0,411 m³		
Min. Quantity	18.200.00 pcs.	Max. Quantity	18.200.00 pcs.		

Tender Text

Turning lock, for subsequent or additional installation in the fitting cover of cable trays, for distributor tray covers as well as for wide span extension T-piece cover, including electro galvanised mushroom head screw with slot FL 6X12-S DIN 603 and electro galvanised safety nut SMS 6 DIN EN ISO 10511. Use outdoors, due to external influences such as wind loads, is only possible with an additional safety device (self-tapping screws, steel band etc.). When fastening, please note that a minimum distance of \geq 50 mm to the cover start/end must be maintained.

Furthermore, it must be ensured that the screw head slot is mounted flush with the fastening lug of the turnbuckle plate. This ensures that all twist-locks on the cover are properly closed (position of the screw head slot) at a later date.

Used for: Fitting covers of cable trays
Distributor tray covers RDSV 50, RDSV 100

Wide span extension T-piece cover WTARDV ...

Delivery: unassembled and loose

Material bolt : steel, pre-galvanised acc. to DIN EN 10346

NIEDAX Model No. : RDRS 2

EP Material_____ EP Wage____

Unit price/piece

Safety & Environment

REACH Date	27.06.2024
REACH Info	Conformable
RoHS Info	Conformable

Aktualisiert am 28/4/2025 Page 2 / 3

Technical Datasheet Cable Tray System

RDRS 2

the photorealistic images are to be considered as reference images

Origin & International Trade		
Country of origin	DE	
Customs tarif number	83024900	

Aktualisiert am 28/4/2025 Page 3 / 3