

Screw Distance Clamp

with female connection thread M6




SAS 38

EAN Code: 4013339734603

Smallest packaging unit: 25 pcs.



the photorealistic images are to be considered as reference images



Article Description

Screw distance clamp, for cables-Ø 29-38 mm, steel, galvanised acc. to DIN EN ISO 2081, thick-film passivated

Technical Datasheet

Conduit and cable distance clamps

SAS 38

the photorealistic images are to be considered as reference images

Additional Price Information

Article group	N06
quantity unit	pcs.

Weight

Weight per quantity unit	52 g / pcs.
Weight in kg per 100	5,13 kg / 100pcs.

Physical Article Dimensions

Height	45.00 mm
Width	67.50 mm
Depth/length	16.00 mm

Packing Dimension

25 pieces = 1		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU			
Lenght	138.00 mm	Width	128.00 mm	Height	71.00 mm
Gross weight	1,32 kg	Volume	0,001 m³		
Min. quantity	25.00 pcs.	Max. Quantity	25.00 pcs.		

250 pieces = 1 covering box					
Lenght	375 mm	Width	282 mm	Height	133.00 mm
Gross weight	13 kg	Volume	0,014 m³		
Min. Quantity	250.00 pcs.	Max. Quantity	250.00 pcs.		

12000 pieces = 1					
Lenght	750 mm	Width	750 mm	Height	730 mm
Gross weight	684 kg	Volume	0,411 m³		
Min. Quantity	12.000.00 pcs.	Max. Quantity	12.000.00 pcs.		

Tender Text

Conduit- and cable distance clamp, with M 6 internal thread, for screwing onto screw anchors up to 8 mm thread length, when installing on push-through anchors DAM 6X... or screw anchor NSA 6X55/SW10-M6, care must be taken to ensure that the connection thread of the push-through anchor does not protrude into the clamping area of the cable.

Please observe additional regulations for use in functional maintenance!

Used for: cables and electrical conduits according to DIN EN 61386-21

Dimensions (approx. dimensions)

Width W x length L : 16 x 69 mm

Internal connection thread : M 6

for cable clamping range-Ø : 29 - 38 mm

for pipe-Ø : 32 mm

Material : steel, electro-galvanised to DIN EN ISO 19598, thick-film passivated

Material screws : steel, electro-galvanised to DIN EN ISO 4042, thick-film passivated

Niedax Model No. : SAS 38

EP Material _____ EP Lohn _____

Technical Datasheet

Conduit and cable distance clamps

SAS 38

the photorealistic images are to be considered as reference images

Tender Text

Unit price/piece

Safety & Environment

REACH Date	27.06.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tarif number	73269098