

Screw Distance Clamp

with female connection thread M6




SAS 60

EAN Code: 4013339735501

Smallest packaging unit: 20 pcs.



the photorealistic images are to be considered as reference images



Article Description

Screw distance clamp, for cables-Ø 55-63 mm, steel, galvanised acc. to DIN EN ISO 2081, thick-film passivated

Technical Datasheet

Conduit and cable distance clamps

SAS 60

the photorealistic images are to be considered as reference images

Additional Price Information

Article group	N06
quantity unit	pcs.

Weight

Weight per quantity unit	84 g / pcs.
Weight in kg per 100	8,31 kg / 100pcs.

Physical Article Dimensions

Height	72.00 mm
Width	97.00 mm
Depth/length	18.00 mm

Packing Dimension

20 pieces = 1		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU	
Lenght	256 mm	Width	138.00 mm
Gross weight	1,75 kg	Volume	0,003 m³
Min. quantity	20.00 pcs.	Max. Quantity	20.00 pcs.

200 pieces = 1 covering box			
Lenght	370 mm	Width	282 mm
Gross weight	18 kg	Volume	0,027 m³
Min. Quantity	200.00 pcs.	Max. Quantity	200.00 pcs.

4800 pieces = 1 pallet			
Lenght	1200 mm	Width	800 mm
Gross weight	443 kg	Volume	0,960 m³
Min. Quantity	4.800.00 pcs.	Max. Quantity	4.800.00 pcs.

Tender Text

Conduit- and cable distance clamp, with M 6 internal thread, for screwing onto screw anchors up to 8 mm thread length, when installing on push-through anchors DAM 6X... or screw anchor NSA 6X55/SW10-M6, care must be taken to ensure that the connection thread of the push-through anchor does not protrude into the clamping area of the cable.

Please observe additional regulations for use in functional maintenance!

Used for: cables and electrical conduits according to DIN EN 61386-21

Dimensions (approx. dimensions)

Width W x length L : 18 x 100 mm

Internal connection thread : M 6

for cable clamping range-Ø : 55 - 63 mm

for pipe-Ø : 63 mm

Material : steel, galvanised according to DIN EN ISO 19598, blue passivated

Material screws : steel, galvanised according to DIN EN ISO 4042, blue passivated

Niedax Model-No. : SAS 60

EP Material_____ EP Wage_____

Unit price/piece

Technical Datasheet

Conduit and cable distance clamps

SAS 60

the photorealistic images are to be considered as reference images

Safety & Environment

REACH Date	27.06.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098