Technical Datasheet
Cable Ladder System


Crossing


with continuously perforated side profiles


KLK 60.303 E3

EAN Code: 4013339343409
Smallest packaging unit:1 pc.

the photorealistic images are to be considered as reference images







Article Description

Crossing for cable ladder, 60x300 mm, stainless steel, material code: 1.4301, AISI 304

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	11 kg / pcs.
Weight in kg per 100	1083 kg / 100pcs.

Physical Article Dimensions

Height	120.00 mm
Width	1590 mm
Depth/length	1590 mm

Technical Datasheet
Cable Ladder System

KLK 60.303 E3

the photorealistic images are to be considered as reference images

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	1590 mm	Width	1590 mm	Height	120.00 mm
Gross weight	11 kg	Volume	0,303 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

```
Crossing, with continuously perforated and profiled side rails, with riveted
rungs made of C-profiles with 11 mm slot width, for creating horizontal 90°
crossings. Please order splice plates KSV 60... separately.
Corresponding U-clamps: B... and BA...
Used for : cable ladder KL 60...
Dimensions (approx. dimensions)
Height H x width W : 60 x 300 mm
Outside dimensions : 1290 mm + W
Length in outgoing direction : 645 mm + W
Inner rail radius R : 500 mm
Material : Stainless steel, material no. 1.4301, AISI 304
NIEDAX Model no. : KLK 60.303 E3
EP Material__________ EP Wage__________
Unit price/piece
```

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Federal State of Origin	RP
Customs tarif number	73089059

Related items

Connector

Model No.	Description
KSV 60 E3	Splice plate for cable ladder, height 60 mm, stainless steel, mat. code: 1.4301, AISI 304, washed,incl. accessories