


Universal-U-Clamp

with pressure trough

BU 22 E5

EAN Code: 4013339890163
Smallest packaging unit: 100 pcs.

the photorealistic images are to be considered as reference images



Article Description

Universal-U-clamp, for 1 cable, Ø 16-22 mm, slot width 18-22 mm, stainless steel, Material: 1.4571, w. stainless steel pressure trough

Additional Price Information

Article group	N08
quantity unit	pcs.

Weight

Weight per quantity unit	34 g / pcs.
Weight in kg per 100	3,36 kg / 100pcs.

Technical Datasheet

U-clamps

BU 22 E5

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	25.00 mm
Width	78.00 mm
Depth/length	29.00 mm

Packing Dimension

100 pieces = 1 carton		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	250 mm	Width	250 mm	Height	100.00 mm
Volume	0,006 m ³	Gross weight	3,73 kg		
Min. quantity	100.00 pcs.	Max. Quantity	100.00 pcs.		
8400 pieces = 1 pallet					
Lenght	1200 mm	Width	800 mm	Height	1000 mm
Gross weight	328 kg	Volume	0,960 m ³		
Min. Quantity	8.400.00 pcs.	Max. Quantity	8.400.00 pcs.		

Tender Text

Universal U-clamp, with pressure trough and M 6 pivot bolt with multiple drive.
Counter tray GWU ... please order separately.
Please observe additional regulations for use in functional maintenance!
Used for: C-profile rails with 18 - 22 mm slot width
Dimensions (approx. dimensions)
Assignment : 1 cable
for cable Ø : 16 - 22 mm
Material bracket : stainless steel, material no. 1.4571, AISI 316Ti
Material pressure trough : stainless steel, material no. 1.4571, AISI 316Ti
NIEDAX model no. : BU 22 E5
EP material_____ EP Wage_____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098