


Conduit- and Cable Distance Clamp

with fixing slot

IPA 20 S

EAN Code: 4046933001710
Smallest packaging unit: 50 pcs.

the photorealistic images are to be considered as reference images



Article Description

Conduit- c. distance clamp, pipe-Ø20 mm, cab. clamping range -Ø19-24 mm, steel, pre-galvanised according to DIN EN 10346, with mounting slot

Additional Price Information

Article group	FT-Rohr
quantity unit	pcs.

Weight

Weight per quantity unit	26 g / pcs.
Weight in kg per 100	2,55 kg / 100pcs.

Technical Datasheet

Electrical installation conduit

IPA 20 S

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	34.00 mm
Width	52.20 mm
Depth/length	14.00 mm

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	14.00 mm	Width	53.00 mm	Height	34.00 mm
Gross weight	0,03 kg	Volume	0,000 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		
50 pieces = 1		✓ VP2-preferred PU			
Lenght	138.00 mm	Width	128.00 mm	Height	71.00 mm
Gross weight	1,31 kg	Volume	0,001 m³		
Min. Quantity	50.00 pcs.	Max. Quantity	50.00 pcs.		
500 pieces = 1 covering box					
Gross weight	13 kg	Volume	0,014 m³		
Min. Quantity	500.00 pcs.	Max. Quantity	500.00 pcs.		
Lenght	375 mm	Width	282 mm	Height	133.00 mm

Tender Text

Conduit- and cable distance clamp, with long fixing hole, for fixing plug-in pipes, threaded pipes and socket pipes-fm to a flat wall/ceiling.
Please note: for safety reasons, we recommend using IPA... conduit and cable distance clamp for overhead installations.
Used for: cables and electrical conduits according to DIN EN 61386-21
fixing plug-in pipes IESR ...
threaded conduit IEGR ...
sleeve conduit-fm FM-MR ...
Dimensions (approx. dimensions)
Width W x length L : 14 x 53 mm
Fastening hole : 6.4 x 10 mm
for clamping range-Ø : 19 - 24 mm
for pipe-Ø : 20 mm
Material : steel, pre-galvanised acc. to DIN EN 10346
Material screws : steel, galvanised acc. to DIN EN ISO 4042
Fintech Model No. : IPA 20 S
EP Material_____ EP Wage_____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Technical Datasheet

Electrical installation conduit

IPA 20 S

the photorealistic images are to be considered as reference images

Origin & International Trade	
Country of origin	DE
Customs tariff number	73269098