



Conduit- and Cable Distance Clamp

with fixing slot

IPA 25 S

EAN Code: 4046933001666
Smallest packaging unit: 50 pcs.

the photorealistic images are to be considered as reference images



Article Description

Conduit- a. cable distance clamp, f. conduit-Ø M25, clamp. range 24-29, Stahl, bandverzinkt DIN EN 10346

Additional Price Information

Article group	FT-Rohr
quantity unit	pcs.

Weight

Weight per quantity unit	40 g / pcs.
Weight in kg per 100	4 kg / 100pcs.

Physical Article Dimensions

Height	38.50 mm
Width	60.00 mm
Depth/length	14.00 mm

Technical Datasheet

Electrical installation conduit

IPA 25 S

the photorealistic images are to be considered as reference images

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	14.00 mm	Width	60.00 mm	Height	39.00 mm
Gross weight	0,04 kg	Volume	0,000 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

50 pieces = 1		✓ VP2-preferred PU			
Lenght	192.00 mm	Width	138.00 mm	Height	71.00 mm
Gross weight	2,09 kg	Volume	0,002 m³		
Min. Quantity	50.00 pcs.	Max. Quantity	50.00 pcs.		

500 pieces = 1 covering box					
Gross weight	8,63 kg	Volume	0,020 m³		
Min. Quantity	500.00 pcs.	Max. Quantity	500.00 pcs.		
Lenght	370 mm	Width	282 mm	Height	196.00 mm

Tender Text

Conduit- and cable distance clamp, with long fixing hole, for fixing plug-in pipes, threaded pipes and socket pipes-fm to a flat wall/ceiling.
Please note: for safety reasons, we recommend using IPA... conduit and cable distance clamp for overhead installations.
Used for: cables and electrical conduits according to DIN EN 61386-21
fixing plug-in pipes IESR ...
threaded conduit IEGR ...
sleeve conduit-fm FM-MR ...
Dimensions (approx. dimensions)
Width W x length L : 14 x 60 mm
Fastening hole : 6.4 x 10 mm
for clamping range-Ø : 24 - 29 mm
for pipe-Ø : 25 mm
Material : steel, pre-galvanised acc. to DIN EN 10346
Material screws : steel, galvanised acc. to DIN EN ISO 4042
Fintech Model No. : IPA 25 S
EP Material_____ EP Wage_____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098