


Self-adhesive clips in polyamide, natural or black colour, with acrylate or synthetic rubber based adhesives, for easy fastening of round cables



COLOR

- Natural
- Black

MATERIALS

Material: polyamide 6.6 natural (+1% carbon black for black version)

Halogen free

Material flammability rating: UL 94-V2

Excellent resistance to: aromatic solvents, oils, greases and derivatives

Good resistance to: bases



Limited resistance to: acids

Not resistant to: phenols and to chlorinated solvents

Technical Data



Type A

CODE		NOMINAL DIMENSIONS			
Natural	Black	Type	A (mm)	B (mm)	C (mm)
54303MV		A	19,4	18,8	7,3
5430RB		A	19,4	18,8	7,3
	5431RB	A	19,4	18,8	7,3





Type B

CODE		NOMINAL DIMENSIONS			
Natural	Black	Type	A (mm)	B (mm)	C (mm)
54323MV		B	26,7	26,5	11,7
5432RB		B	26,7	26,5	11,7
	5433RB	B	26,7	26,5	11,7



Type C

CODE		NOMINAL DIMENSIONS				
Natural	Black	Type	A (mm)	B (mm)	C (mm)	D (mm)
54363MV		C	26,5	26,5	17,4	30,6
5436RB		C	26,5	26,5	17,4	30,6
	5439RB	C	26,5	26,5	17,4	30,6



CODE		Material	Adhesive	Installation temperature (°C)	Working temperature (°C)	Bag (pcs)	Box (pcs)
54303MV		PA 6.6	acrylic	+20\+40	-40\+75	100	12.000
5430RB		PA 6.6	rubber base	+15\+40	-40\+60	100	12.000
	5431RB	PA 6.6	rubber base	+15\+40	-40\+60	100	12.000
54323MV		PA 6.6	acrylic	+20\+40	-40\+75	100	5.000
5432RB		PA 6.6	rubber base	+15\+40	-40\+60	100	5.000
	5433RB	PA 6.6	rubber base	+15\+40	-40\+60	100	5.000
54363MV		PA 6.6	acrylic	+20\+40	-40\+75	100	3.000
5436RB		PA 6.6	rubber base	+15\+40	-40\+60	100	3.000
	5439RB	PA 6.6	rubber base	+15\+40	-40\+60	100	3.000

NOMINAL DIMENSIONS				
Adhesive	Support type	Density (Kg/m³)	U.V. resistance.	Mode of use.
Rubber base	Polyethylene	100	Restricted (not recommended)	For instant application
Acrylic	Polyurethane	320	Good	Allow to rest at least 24h