



HW Double device socket E118

Order number: 7350179
 Type: E118

- The basics for a proper hollow wall installation
- With break-outs for cables and pipes
 - Integrated cable restraint for NYM cables
 - Secure fixing of tubes

Dimensions

Depth	49 - 49 mm
Diameter	68 mm
Internal depth	48 mm
Length	142 mm
Milling hole diameter	2x Ø 68 mm
Width	71 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material

Socket material	PP
-----------------	----

Properties

Can be lead sealed	-
Colour	Orange
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	HW
PVC-free	true
Silicone-free	true
Stackable	-

Technical features

Cable entry 3x1.5²	4
Cable entry 5x1.5²/3x2.5²	4
Cable entry 7x1.5²/5x2.5²	2
Design voltage	400 V
max. cross section	2,5 mm²
Pipe entry M20	6
Pipe entry M20/M25	4
Suitable for sheet thickness	5-40 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	false
RoHS	true
Standards	• DIN EN 60670-1(VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None
---------------	------