



Damp area distribution box IP66, grey, NEPTUN Compact

Order number: 7340191

Type: NFK11gr

NEPTUN Compact - Small size. Great resistance.

- Robust housing in a modern design
- Screws with assembly position
- Various break-out entries M20-M40
- IP66 protection class with all-round seal
- Custom fixing options for perfect alignment
- Membrane entry on NFK08
- 4 different sizes
- Use in damp areas and in protected outdoor areas

Dimensions

| | |
|--------|--------|
| Depth | 67 mm |
| Height | 110 mm |
| Length | 110 mm |
| Width | 110 mm |

Environmental conditions

| | |
|-------------------------------|--------|
| Ambient temperature (maximum) | 60 °C |
| Ambient temperature (minimum) | -25 °C |

Material

| | |
|--------------|----|
| Box material | PS |
| Lid material | PS |

Properties

| | |
|---------------------------|---------------------|
| Can be lead sealed | true |
| Colour | Grey |
| Degree of protection (IP) | IP66 |
| Free of heavy metals | true |
| Halogen-free | true |
| Installation type | SM |
| Insulation | Protection class II |
| PVC-free | true |
| Silicone-free | true |

Technical features

| | |
|--------------------|-------------------|
| Design voltage | 690 V |
| max. cross section | 6 mm ² |

Certificates & standards

| | |
|----------------|--------|
| CE | true |
| Glow wire test | 650 °C |
| REACH | false |
| RoHS | true |
| VDE | true |

Accessories

| | |
|---------------|------|
| Equipped with | None |
|---------------|------|