



### FM small distributor JUMBO with screw clamp

Order number: 7210029

Type: UPV24+4ST

Simple and reliable for flush mounting

suitable for: Devices up to 63A

#### Dimensions

Depth	98 mm
Height	525 mm
Height of mounting recess	518 mm
Plaster compensation	15 mm
Width	365 mm
Width of mounting recess	359 mm

#### Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

#### Material

Box material	PS
Cover material	PS
Door material	Powder-coated steel

### Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	true
Impact resistance	IK07
Installation type	FM
Insulation	Protection class II
Number of compartments	28
Number of rows	2
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

### Technical features

Cable entry	backside: 8x M25
Design current	63 A
Design voltage	400 V
Permissible power loss according to DIN 43 873	without inner horizontal partitions 10 K = 5.0 watts 15 K = 8.0 watts 20 K = 11.5 watts 25 K = 15.0 watts 30 K = 19.0 watts

### Certificates & standards

CE	true
Glow wire test	650 °C
REACH	false
RoHS	true
Standards	<ul style="list-style-type: none"> <li>• DIN EN 60670-1</li> <li>• DIN EN 60670-24</li> <li>• DIN EN 61439-1</li> <li>• DIN EN 61439-3                             <ul style="list-style-type: none"> <li>• DIN 43871</li> </ul> </li> </ul>
VDE	true

### Accessories

Equipped with	1x door with frame (T+R.JUMBO24+4) 1x PE-N screw terminal (KN17PE)
---------------	---