

Horizontal and Vertical Cable Ladder

rung spacing 300 mm, with continuously perforated and profiled side rails, with cross perforated, riveted, upwards-open rungs made of C-profiles with a 16 mm slot width

★ KSL 60.403/6 S


EAN Code: 4013339259892

Smallest packaging unit:6 m

quantity unit:m M



the photorealistic images are to be considered as reference images



Article Description

Horiz.vertical cabel ladder, 60x400x6000 mm,perf., SA 300 mm,t=1,5 mm, steel, pre-galvanised acc. to DIN EN 10346

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	3,116 kg / m
Weight in kg per 100	312 kg / 100m

Technical Datasheet

Cable Ladder System

★ KSL 60.403/6 S


the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	60.00 mm
Width	400 mm
Depth/length	6000 mm

Load Specifications

Load diagram: q = evenly distributed cable load (tested acc. to DIN IEC 61537)



Fixing distance (m)

The load details shown in the diagram are independent of the position of the connectors.

The load specifications apply only to horizontal and vertical cable ladder with 300 mm rung spacing.

Packing Dimension

6 meters = 1 piece

✓ VP1-smallest packaging unit (PU)

Lenght	6000 mm	Width	400 mm	Height	60.00 mm
Gross weight	19 kg	Volume	0,144 m³		
Min. quantity	6.00 m	Max. Quantity	6.00 m		

60 meters = 1 bundle

Min. Quantity	60.00 m	Max. Quantity	60.00 m
---------------	---------	---------------	---------

Tender Text

Horizontal and vertical cable ladder according to DIN EN 61537, with continuously perforated and profiled side rails, with cross perforation, riveted upwardly open rungs made of C-profiles with 16 mm slot width.

Additional perforations $\varnothing$ 8.5 mm in the base of the side rails allow variable fastening directly to the ground.

Cross perforations in the rungs allow further extensions and substructures. The load capacity specifications B/2 apply when used as a vertical cable ladder.

For horizontal use of the cable ladder, please refer to the load capacity data in the load diagram.

Delivery length = transport length

Technical Datasheet

Cable Ladder System



the photorealistic images are to be considered as reference images

Tender Text

Corresponding U-clamps: B... and BK...
Dimensions (approx. dimensions)
Height H (outside) x width W (outside) : 60 x 400 mm
Material thickness t side rail: 1.5 mm
Rung distance: 300 mm
Side rail perforation: 9 x 15 mm
Center distance: 25 mm
Base perforation : Ø 8.5 mm
Center distance : 100 mm
Base perforation : Ø 5.4 mm
Center distance : 50 mm
Load capacity with B/2 : 1 kN
Delivery length L : 6000 mm
Usable cross-section : 17200 mm²
Material : Steel, pre-galvanised according to DIN EN 10346
NIEDAX Model No. : KSL 60.403/6 S
Material_____ EP Wage_____
Unit price/metre

Safety & Environment

REACH Date	04.02.2026
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Cover

Model No.	Description
RD 400	Cover for cable tray/-ladder, with joint strip, 402x3000 mm, steel, pre-galvanised according to DIN EN 10346
RDRS 9	Turning bolt with locking nut acc. to DIN EN ISO 10511, steel, pre-galvanised according to DIN EN 10346, incl. accessories
RDV 400	Cover for cable tray/-ladder, with joint strip, 402x3000 mm, steel, pre-galvanised according to DIN EN 10346

Barrier strip

Model No.	Description
KLWC 16	Barrier strip fastening clamp, for 16 mm slot width, steel, pre-galvanised according to DIN EN 10346, incl. accessories
RTV 35 E2	Splice plate for barrier strip, 29x80 mm, stainless steel, material code: 1.4310
RW 35	Barrier strip, 30x3000 mm, t=0,75 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories

Technical Datasheet

Cable Ladder System

★ KSL 60.403/6 S

the photorealistic images are to be considered as reference images

Related items

Connector

Model No.	Description
KSV 60 S	Splice plate for cable ladder, height 60 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories
KSV 60/320 S	Splice plate for cable ladder, 60x320mm, steel, pre-galvanised according to DIN EN 10346