


SAAF™ Cassette Medium Duty

1-INCH V-BANK, 18-INCH DEEP GAS FILTRATION CASSETTE

- Form and fit unlike any other 18"-deep, 1" gas filtration cassette
- Improved fit and sealing, even when deployed in older cassette holding systems
- Enhanced media utilization design
- No-glue design eliminates problems from spills, off-gassing, bypass, and leakages
- Patented cassette design and manufacturing process. Patents covered under US 7,588,629 B2.
- Filled cassettes are UL Classified

SAAF Cassette Medium Duty is the best 1" V-bank, 18"-deep gas filtration cassette in the industry. AAF designs, manufactures, and performs quality control compliance on cassettes under ISO 9001:2000 and other applicable global quality certifications.




High Tech Features

The SAAF Cassette Medium Duty is constructed from High Impact Polystyrene (HIPS) and comes prefilled with SAAF chemical media. High technology design tools were employed to validate the design and confirm better performance. Computational Fluid Dynamics (CFD) modeling and performance tests confirm optimal design. The resulting design and construction surpasses any competitor's cassettes in the market, while allowing users a truly better design with value-enhancing features. The design retrofits easily and performs better than older legacy cassettes in existing installations.

Efficiency and Performance

Most legacy cassette manufacturers state that their cassettes operate at >90% removal efficiencies. In reality, these efficiencies are not cassette efficiencies. In an installation, removal efficiency is dependent on the precise sealing of the chemical media delivery mechanism, i.e., the cassette with the cassette holding mechanism. Due to looser manufacturing tolerances, testing of most legacy cassettes shows removal efficiencies as low as 65%.

SAAF™ Cassette Medium Duty



Design, Construction, and Patents

SAAF Cassettes perform and operate at optimum gas filtration efficiency, due to various patent pending features.

SAAF-V – Patented enhanced media utilization design eliminates the “nose cavity” typically created by legacy cassettes. Nose cavities “cocoon” up to 30% of the chemical media, keeping it isolated from airflow contact at all times during the life of the cassette. SAAF Cassettes are the only cassettes that utilize 92% of all chemical media in the cassette – outperforming legacy cassettes by 25%.

SAAF-T-Snap – Patented design provides a high pressure, no-glue snap assembly. This rigid construction excludes harmful glues, solvents, or Methyl Ethyl Ketone (MEK) from the manufacturing process. The SAAF-T-Snap design, unlike legacy cassettes, has no see-through holes in the solid end plates. This allows for better structural integrity and eliminates gas by-pass problems. The entire SAAF Chemical Media in the cassette can be used specifically to overcome external gaseous contaminants, not contaminants from the cassette itself. SAAF Cassettes are the ideal choice in high-precision applications where zero off-gassing products are mandatory.


SAAF-T-Butterfly Seal and SAAF-T-Groove – Designs provide near absolute sealing, even in existing retrofit applications.

SAAF-T-Seal – Patent pending plastic rivets secure the solid fill caps at multiple points and secure against bursts or leaks in normal usage. Older legacy cassettes use stickers, labels, or low friction end caps that have high instances of failure and chemical media spillage.

SAAF-T-Track – System utilizes the **SAAF-T-Groove** feature and provides a compression fit that eliminates bypass. The solid top and bottom rail system on SAAF Cassettes eliminates yet another bypass zone.

Cassette-To-Cassette Mating Seals – Smooth mating end panels with no penetrations or outward turned flanges allow excellent cassette-to-cassette sealing.

SAAF-T-Screens – Patented design and precision engineering allow optimized apertures for better media retention and better energy efficiency through improved aerodynamics and reduced pressure drop.




Applications

SAAF Cassette Medium Duty is used for gas removal applications in:

- Energy savings related applications.
- Odor control applications at wastewater treatment plants.
- Odor control for exhaust air streams.
- Removal of corrosive contaminants for computer rooms and data centers.
- Outdoor air purification for cleanroom or pharmaceutical airflows.
- Higher contaminant concentration in institutional or commercial establishments for improved indoor air quality.
- Air purification in museums, archives, or historical facilities.

(1) Velocity Magnitude -in./s.



AAF's patented cassette design offers improved airflow characteristics to ensure full media utilization.

Disposal and Recycle Instructions

- 1 Remove the cassette after use.
- 2 Empty out the SAAF chemical media by removing the SAAF-T-Seal rivets.
- 3 Depending on the SAAF chemical media in use, the media may be sent to a regular landfill or disposed of according to applicable local, state, and federal regulations.
- 4 The empty cassette can then be sent for plastic recycling or for incineration.
- 5 The empty cassette is completely incinerable/recyclable.

SAAF™ Cassette Medium Duty

General Specifications and Application Parameters

Nominal Size

6 x 24 x 18 inches (One cassette is made up of two halves for easy lifting)

Airflow

Designed for 500 FPM (2.5 m/s) face velocity or 500 CFM (850 m³/h) airflow per cassette

Pressure Drop

0.31 in. w.g. @ 500 FPM (77 Pa @ 2.5 m/s) face

Construction

100% recyclable/incinerable HIPS plastic

UL Rating

UL Classified in accordance with UL Standard 900 and ULC-S111*

Chemical Filter Bed Depth

1" (25 mm) nominal

Chemical Media Capacity

0.5 cubic feet (0.014 m³)

Contains Chemical Media

Various (as stated in submittal or as approved)

Humidity Range

5% – 99% RH


Temperature

-4°F to 125°F

*Consult an AAF sales representative for media/module combinations.

Performance Data

Initial Resistance vs. Face Velocity



9920 Corporate Campus Drive, Suite 2200, Louisville, KY 40223-5690
888.223.2003 Fax 888.223.6500 | aafintl.com

AAF has a policy of continuous product research and improvement. We reserve the right to change design and specifications without notice.

©2023 AAF International and its affiliated companies.

ISO Certified Firm

GPF-1-108G 11/23