THE WORLD LEADER IN CLEAN AIR SOLUTIONS

SureAire™

DIFFUSER SECTIONS

- Units are constructed of durable 16-gauge galvanized steel
- "Z" channel support members reinforce all four corners
- Diffuser plate helps distribute air more evenly across the final filter bank
- Diffuser plate open area is 51%
- Minimal static pressure

Options

- Double-walled insulation and aluminum or 304 stainless steel housing construction
- Special size diffuser sections are available to match Surelock HEPA filter housings
- Diffuser sections may be factory assembled to downstream SureSeal™ filter housings

SureAire diffuser sections are recommended for use on the positive side of the fan where high velocity or turbulent airflow conditions may occur. SureAire units are furnished with a diffuser plate that promotes evenly distributed

mixing of air. Diffuser sections are factory assembled flanged units suitable for installation in a duct upstream of a SureSeal housing or attached to an air handling unit. Units have a maximum inline depth of 12" and incorporate 11/2" standing flanges on both air entering and air leaving sides of the unit.

Versatility

SureAire sections are available in a wide range of sizes, up to 8 feet high and 12 feet wide. If large units are not practical to install, smaller units are available with modifications to facilitate stacking. Diffuser sections are designed to match up to the SureSeal housing that is installed downstream of the unit.

Construction


SureAire diffuser sections are constructed of 16-gauge galvanized steel with upstream and downstream outwardly-turned flanges for easy installation on the upstream side of the corresponding SureSeal housing. Units include "Z" channel vertical support members on all four corners. Units wider than 4 feet include intermediate support channels. Metal-to-metal joints are sealed with silicone compound. The diffuser plate is fabricated of 16-gauge galvanized steel with .118" diameter holes staggered on ¼" centers. The total open area is 51% with a pressure drop of 0.1" w.g. at 500 FPM.





SureAire™ Diffuser Sections

Construction Details



*Intermediate support(s) are furnished on housings over 4 ft. wide.



AAF has a policy of continuous product research and improvement. We reserve the right to change design and specifications without notice.