
	<b>NORMAL CHECKLIST</b> <b>C-150</b> <b>LN-TSE</b>	Rev.01 13.01.2022
---	--	----------------------

BEFORE START		
1	A/C doc. / Pre-flight / Pax brief	COMPLETED
2	Pitot cover / Chocks / Control lock	REMOVED
3	Seatbelts & Harness	FASTENED
4	Parking Brake	SET
5	Doors	CLOSED & LOCKED
6	Circuit Breakers	CHECKED
7	Electrical Equipment	OFF
8	Avionics	OFF
9	ELT	ARMED
10	Carburetor Heat	OFF
11	Fuel Shutoff Valve	ON
STARTING ENGINE		
1	Engine Fire Procedure	BRIEF
2	Throttle	OPEN 1 cm
3	Master Switch	ON
4	Navigation Lights	ON
5	Mixture	RICH
6	Prime	AS REQ.
7	Starter	ENGAGE
8	Throttle	1000 RPM
9	Oil Pressure	CHECK
10	Primer	LOCKED
11	Avionics & Radio	ON
12	Transponder	ALT & 7000
13	Gyro	SET
TAXI		
1	Mixture	LEAN
2	Brakes & Steering	CHECK
3	Flight Instruments	CHECK
GROUND CHECK		
1	Parking Brake	SET
2	ATIS, Clearance & Start Up	OBTAIN
3	Altimeter	SET QNH
4	Transponder	SET
5	Flight Controls	CHECK
6	Flight Instruments	CHECK
7	Fuel Quantity	CHECK
8	Trim	SET
9	Flaps	TEST & SET
10	Mixture	RICH
11	Throttle	1700 RPM
12	Magnetos	R - BOTH - L - BOTH
13	Vacuum	CHECK
14	Alternator	CHECK
15	Oil Temp & Pressure	CHECK
16	Carburetor Heat	CHECK
17	Throttle	IDLE, Then 1000
18	Mixture	LEAN
19	Departure & Engine Fail Procedure	BRIEF

	<b>NORMAL CHECKLIST</b> <b>C-150</b> <b>LN-TSE</b>	Rev.01 13.01.2022
---	--	----------------------

LINE UP		
1	Flaps	UP / 10 Degrees
2	Mixture	RICH
3	Landing Light	ON
5	Gyro	SET
AFTER TAKEOFF		
1	Cruise power	SET
2	Mixture	LEAN
3	Flaps	UP
4	Landing Light	OFF
APPROACH / BEFORE LANDING		
1	Seat / Seat Belts / Harness	CHECK
2	Landing Light	ON
5	Mixture	RICH
6	Primer	LOCKED
7	Carburetor Heat	AS REQ.
8	Go-Around Procedure	REVIEW
1	• Throttle	FULL
2	• Carburetor Heat	OFF
3	• Flaps	20 Degrees
4	• Climb Speed	Min. 60 KIAS
5	• Flaps 10 until clear of obstacles, when above safe alt. and 65 KIAS	FLAPS UP
AFTER LANDING (RWY vacated)		
1	Flaps	UP
2	Mixture	LEAN
3	Landing Lights	OFF
SHUTDOWN		
1	Parking Brake	SET
2	Transponder	7000
3	Avionics & Radio	OFF
4	Throttle	IDLE
5	Magnetos	CHCK GROUNDING
6	Mixture	CUT-OFF
7	Magnetos	OFF
8	Navigation Lights	OFF
9	Master Switch	OFF

VS0 .....	42 KIAS
VS1 .....	47 KIAS
VX .....	56 KIAS
VY .....	68 KIAS
VA @ 1600 lbs .....	97 KIAS
VA @ 1450 lbs .....	93 KIAS
VA @ 1300 lbs .....	88 KIAS
VL/D .....	60 KIAS
VR .....	55 KIAS
Fuel capacity .....	26 Gal – 156 lbs / 98 L – 71 Kg
Usable fuel .....	22,5 Gal / 85 L
Oil capacity .....	6 Quarts
Minimum oil level .....	4 Quarts
Max T/O weight .....	1600 lbs / 725 Kg