


Structural I-Beam/Mill Finish American Standard (AS)

6061-T6, QQ-A-200/16 — 25' Length


Part#	A"	Description		B"	x	Approx.	Length	Wt./Ft.
		x				c		
**	3	x		2.330	x	.170	25'	1.944#
6088025	3	x		2.509	x	.349	25'	2.670#
6090025	4	x		2.660	x	.190	25'	2.642#
**	5	x		3.000	x	.210	25'	3.508#
**	5	x		3.284	x	.494	25'	5.250#
6098025	6	x		3.330	x	.230	25'	4.421#
**	6	x		3.443	x	.343	25'	5.220#
6102025	6	x		3.565	x	.465	25'	6.072#
6113025	8	x		4.000	x	.270	25'	6.510#
**	10	x		4.660	x	.310	25'	8.981#
**	12	x		5.000	x	.350	25'	11.220#



** Sizes without part numbers available upon request

H Beams & Wide Flange

Description Part#	A"	x	Approx.		c	T1	Length	Wt./Ft.
			B"	x				
6191025	4	x	4	x	.313	.290	25'	4.758#
6176025	6	x	6	x	.269	.240	25'	5.401#
6192024	5	x	5	x	.330	.313	24'	6.494#



Aluminum

Structural I-Beam/Mill Finish American Association (AA)

6061-T6, QQ-A-200/16 - 25' Length

Part#	A"	Description				c	T1	R	Length	Approx. Wt./Ft.
		x	B"	x						
6138025	3	x	2.5	x	.260	.150	.25	25'	2.030#	
7137024	3	x	2.5	x	.200	.150	.25	24'	1.732#	
6142025	4	x	3.0	x	.29	.170		25'	2.793#	
LI86295	6	x	4.0	x	.290	.190	.30	22'	4.030#	
6146025	6	x	4.0	x	.290	.190	.30	25'	4.030#	
61460142	6	x	4.0	x	.290	.190	.30	14' 2"	4.030#	
LI81822	6	x	4.0	x	.350	.210	.30	12' 6"	4.700#	
LI81907	6	x	4.0	x	.350	.210	.30	11'	4.700#	
LI81908	6	x	4.0	x	.350	.210	.30	12'	4.700#	
LI81877	6	x	4.0	x	.350	.210	.30	22'	4.700#	
6148025	6	x	4.0	x	.350	.210	.30	25'	4.700#	
LI81906	8	x	5.0	x	.350	.230	.30	12' 1"	6.181#	
6152012	8	x	5.0	x	.350	.230	.30	12' 6"	6.181#	
6152025	8	x	5.0	x	.350	.230	.30	25'	6.181#	
6154012	8	x	5.0	x	.410	.250	.30	12' 6"	7.023#	
6154025	8	x	5.0	x	.410	.250	.30	25'	7.023#	
LI81910	8	x	5.0	x	.410	.250	.30	26'	7.023#	
LI81823	8	x	5.0	x	.410	.250	.30	12' 6"	7.023#	
LI81909	10	x	6.0	x	.410	.250	.40	14'	8.650#	
6158016	10	x	6.0	x	.410	.250	.40	16'	8.650#	
LI81902	10	x	6.0	x	.410	.250	.40	28'	8.650#	
6158025	10	x	6.0	x	.410	.250	.40	25'	8.650#	
6160016	10	x	6.0	x	.500	.290	.40	16'	10.286#	
6160025	10	x	6.0	x	.500	.290	.40	25'	10.286#	
6160032	10	x	6.0	x	.500	.290	.40	32'	10.286#	
6163025	12	x	7.0	x	.470	.290	.35	25'	11.672#	
6163011	12	x	7.0	x	.620	.310	.40	16'	14.292#	
6164025	12	x	7.0	x	.620	.310	.40	25'	14.292#	

