



OUTSIDE

INSIDE

7200ER
Emergency Release****

Heavy Duty
SS "Hooks"

2001.212
Sliding Door
Lock
(5 1/2" x 1"
faceplate)

7200ADA
Handle

2001SD
Strike

2001DB
Dust Box

7200P

The TOTAL pocket door opening must be 36" MINIMUM. The door must protrude a min. of 4" to attach the ADA pocket door hardware.**

The pocket door opening must have a Clear Width of 32" according to the ADA Standard 404.2.3*

34" to finished floor***

The ADA Standard 404.2.3 is from the Dept. of Justice ADA Publication of Sept. 15, 2010. Accurate Lock and Hardware Co. LLC encourages the end user to double check all state and federal standards for your particular project.

**The total opening has to be 4" greater than the Federal "Clear Width" dimension to work properly.

***The bottom of the 7200P pull handle must be installed 34" from the finished floor. This will give 48" (the maximum) from the finished floor to top of 7200ADA handle, thus meeting Code 404.2.7.

**** Occupancy indicator: if an occupancy indicator is needed, please substitute the 7200ER with a #7200ER-i. If you have questions please call for details.

Parts List

QTY	Part Number	Finish	Description
1	2001.212		Sliding door lock 2 1/2 BS
1	7200ADA		Inside ADA Handle
1	7200ER		Outside coin release
1	2001SD		Strike Plate
1	2001DB		Dust box
1	7200P		Back to Back ADA Pull



ACCURATE
LOCK & HARDWARE
AMERICAN CRAFTED SINCE 1972

2001ADAP-5
ADA Thumbturn x ER Coin Release x Back to Back Pulls

Spec.2001ADAP-5