

DIN 7984 A2
Zylinderschrauben, Innensechskant, niedriger Kopf

DIN 7984
A2

DIN 7984 A2
Hexagon socket head cap screws with low head

d	M 10	M 12	M 16	M 20	M 24
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3					
4					
5					
6					
8					
10					
12	7984210 12				
14	7984210 14				
16	7984210 16	7984212 16			
18	7984210 18	7984212 18			
20	7984210 20	7984212 20	7984216 20		
22	7984210 22	7984212 22			
25	7984210 25	7984212 25	7984216 25		
30	7984210 30	7984212 30	7984216 30	7984220 30	
35	7984210 35	7984212 35	7984216 35	7984220 35	
40	7984210 40	7984212 40	7984216 40	7984220 40	7984224 40
45	7984210 45	7984212 45	7984216 45	7984220 45	7984224 45
50	7984210 50	7984212 50	7984216 50	7984220 50	7984224 50
55	7984210 55	7984212 55	7984216 55	7984220 55	7984224 55
60	7984210 60	7984212 60	7984216 60	7984220 60	7984224 60
65	7984210 65	7984212 65	7984216 65	7984220 65	7984224 65
70	7984210 70	7984212 70	7984216 70	7984220 70	7984224 70
75	7984210 75	7984212 75	7984216 75	7984220 75	7984224 75
80	7984210 80	7984212 80	7984216 80	7984220 80	7984224 80
90	7984210 90	7984212 90	7984216 90	7984220 90	7984224 90
100	7984210 100	7984212 100	7984216 100	7984220 100	7984224 100
110	7984210 110	7984212 110	7984216 110	7984220 110	7984224 110
120	7984210 120	7984212 120	7984216 120	7984220 120	7984224 120
130			7984216 130	7984220 130	7984224 130
140			7984216 140	7984220 140	7984224 140
150			7984216 150	7984220 150	7984224 150



b = nach Norm
- "0" = reduzierte
Belastbarkeit

b = at Norm
- "0" = reduced load capacity

DIN

dk	16	18	24	30	36
k	6	7	9	11	13
Antrieb	SW 7	SW 8	SW 12	SW 14	SW 19