

## VSH SudoPress Copper coupling with nut FF 12xG3/8"



this article is part of a product group (SP4359GV) that contains a total of 17 items

[view all 17 items](#) 

**group:** SP4359GV **item:** 6671258 **category:** fittings

including flat seal ring

### applications

potable water, heating, cooling,  
compressed air, solar energy,  
vacuum

### segments

commercial building , industry ,  
shipbuilding

### approvals

ACS , DVGW Wasser , QB  
(CSTBat) , RISE , TSU , WRAS

### specifications - characteristics

<b>color</b>	brass, bronze
<b>materials</b>	bronze, brass (CW617N, EN CC499K)
<b>finishing</b>	none
<b>manufacturer</b>	Aalberts integrated piping systems B.V. (VSH)
<b>shape</b>	straight
<b>connection type</b>	press (V), coupling nut
<b>sealing</b>	EPDM

### specifications - general

<b>product group</b>	fittings (unions)
<b>ETIM class</b>	ECO03024 Fitting with 2 connections
<b>HS code</b>	74122000
<b>brand</b>	VSH
<b>series</b>	SudoPress Copper
<b>product type</b>	SP4359GV
<b>UNSPS</b>	40174907
<b>scip</b>	5cf0b298-027a-4aed-9537-63ab9cac8f2d

### specifications - product info

<b>item</b>	VSH SudoPress Copper coupling with nut FF 12xG3/8"
<b>item number with gtin</b>	6671258 (03430651365574)
<b>product number with gtin</b>	4359GVW1238 (03430650434240)
<b>item group</b>	SP4359GV - VSH SudoPress Copper coupling with nut (press x female thread)
<b>size</b>	12xG3/8"
<b>weight</b>	0.04 kg
<b>dimensions</b>	40x25x25 mm
<b>packaging</b>	bag (5 pce)

### specifications - technical

<b>max operating pressure liquid</b>	16 bar
<b>min. medium temperature</b>	-20 °C
<b>max medium temperature</b>	110 °C
<b>peak medium temperature</b>	135 °C

### dimensions

d1	DN1	I1	z1	d2	DN2	I2	z2	slw2
12.0	DN10	31	11	17.2	3/8"	9	4	19

