

W4


NPSS  
DIN 3017

## COLLIER DE SERRAGE BANDE NON PERFOREE DE 5 MM, 9 MM OU 12 MM

WORM DRIVE HOSE CLIPS NON PERFORATED BAND 5, 9 OR 12MM

SCHNECKENGEWINDESCHELLEN GEPRÄGTES BAND 5, 9 ODER 12MM

ABRAZADERA SIN FIN, CINTA NO PERFORADA DE 5, 9 O 12MM



d	Code	s	e	l	Cond.	Sur-cond.	kg/100	€/100
7-11	NPSS5 7-11	4	0,4	5,1	50	1000	0,270	136,07
10-19	NPSS5 10-19	4	0,4	5,1	50	1000	0,310	140,69
8-12	NPSS9 8-12	7	0,73	9,15	50	1000	1,200	91,62
10-16	NPSS9 10-16	7	0,73	9,15	50	1000	1,300	93,16
12-22	NPSS9 12-22	7	0,73	9,15	50	1000	1,400	95,25
16-27	NPSS9 16-27	7	0,73	9,15	50	1000	1,500	99,28
20-32	NPSS9 20-32	7	0,73	9,15	50	1000	1,600	111,17
25-40	NPSS9 25-40	7	0,73	9,15	25	500	1,700	121,59
32-50	NPSS9 32-50	7	0,73	9,15	25	500	1,800	128,48
40-60	NPSS9 40-60	7	0,73	9,15	25	500	1,900	136,84
50-70	NPSS9 50-70	7	0,73	9,15	20	400	2,100	145,50
60-80	NPSS9 60-80	7	0,73	9,15	20	400	2,300	152,86
70-90	NPSS9 70-90	7	0,73	9,15	10	200	2,400	160,63
80-100	NPSS9 80-100	7	0,73	9,15	10	200	2,500	163,70
90-110	NPSS9 90-110	7	0,73	9,15	10	200	2,700	168,59
100-120	NPSS9 100-120	7	0,73	9,15	10	200	2,800	180,00
110-130	NPSS9 110-130	7	0,73	9,15	10	200	2,900	183,33
120-140	NPSS9 120-140	7	0,73	9,15	10	200	3,100	191,58
16-27	NPSS12 16-27	7	0,73	12,15	25	500	1,800	112,84
20-32	NPSS12 20-32	7	0,73	12,15	25	500	1,900	116,67
25-40	NPSS12 25-40	7	0,73	12,15	25	500	2,000	127,47
30-45	NPSS12 30-45	7	0,73	12,15	25	500	2,100	130,62
32-50	NPSS12 32-50	7	0,73	12,15	25	500	2,200	136,96
40-60	NPSS12 40-60	7	0,73	12,15	10	200	2,500	144,88
50-70	NPSS12 50-70	7	0,73	12,15	10	200	2,700	147,87
60-80	NPSS12 60-80	7	0,73	12,15	10	200	3,000	168,69
70-90	NPSS12 70-90	7	0,73	12,15	10	200	3,200	179,98
80-100	NPSS12 80-100	7	0,73	12,15	10	200	3,400	183,20
90-110	NPSS12 90-110	7	0,73	12,15	10	200	3,700	191,81
100-120	NPSS12 100-120	7	0,73	12,15	10	200	3,900	202,60
110-130	NPSS12 110-130	7	0,73	12,15	10	200	4,100	213,82
120-140	NPSS12 120-140	7	0,73	12,15	10	200	4,400	225,55
130-150	NPSS12 130-150	7	0,73	12,15	10	100	4,600	234,96
140-160	NPSS12 140-160	7	0,73	12,15	10	100	4,800	241,42
150-170	NPSS12 150-170	7	0,73	12,15	10	100	5,000	247,06
160-180	NPSS12 160-180	7	0,73	12,15	10	100	5,200	261,50
170-190	NPSS12 170-190	7	0,73	12,15	10	100	5,400	270,06
180-200	NPSS12 180-200	7	0,73	12,15	10	100	5,600	266,19
190-210	NPSS12 190-210	7	0,73	12,15	10	100	5,800	367,98
200-220	NPSS12 200-220	7	0,73	12,15	10	100	6,000	376,20



Couple de serrage recommandé / recommended torque :  
5 mm = 0.9Nm ; 9 mm = 4Nm ; 12 mm = 5.5Nm