

DIN 7982  
A4  
Alternative Norm  
ersetzt durch ISO 7050

DIN 7982 A4 PZ  
Senk-Blebschrauben mit Kreuzschlitz  
DIN 7982 A4 PZ  
Cross recessed countersunk head tapping screws



TX Form siehe ISO 14586  
- Blechgewinde  
- PZ  
- Senkkopf  
TX type see ISO 14586  
- Sheet thread  
- PZ  
- Countersunk head

| d    | 2,2                 | 2,9                 | 3,5                 | 3,9                 |
|------|---------------------|---------------------|---------------------|---------------------|
| l/mm | Art. Nr. / Item no. | Art. Nr. / Item no. | Art. Nr. / Item no. | Art. Nr. / Item no. |
| 4,5  | 79824022 45         |                     |                     |                     |
| 6,5  | 79824022 65         | 79824029 65         | 79824035 65         | 79824039 65         |
| 9,5  | 79824022 95         | 79824029 95         | 79824035 95         | 79824039 95         |
| 13   | 79824022 13         | 79824029 13         | 79824035 13         | 79824039 13         |
| 16   | 79824022 16         | 79824029 16         | 79824035 16         | 79824039 16         |
| 19   | 79824022 19         | 79824029 19         | 79824035 19         | 79824039 19         |
| 22   | 79824022 22         | 79824029 22         | 79824035 22         | 79824039 22         |
| 25   | 79824022 25         | 79824029 25         | 79824035 25         | 79824039 25         |
| 28   |                     |                     |                     | 79824039 28         |
| 32   |                     | 79824029 32         | 79824035 32         | 79824039 32         |
| 35   |                     |                     |                     |                     |
| 38   |                     | 79824029 38         | 79824035 38         | 79824039 38         |
| 42   |                     |                     |                     |                     |
| 45   |                     |                     | 79824035 45         | 79824039 45         |
| 50   |                     |                     | 79824035 50         | 79824039 50         |
| 55   |                     |                     |                     | 79824039 55         |
| 60   |                     |                     | 79824035 60         | 79824039 60         |
| 70   |                     |                     | 79824035 70         | 79824039 70         |
| 80   |                     |                     |                     |                     |
| 90   |                     |                     |                     |                     |
| 100  |                     |                     |                     |                     |
| 110  |                     |                     |                     |                     |
| 120  |                     |                     |                     |                     |


|         |     |     |     |     |
|---------|-----|-----|-----|-----|
|         |     |     |     |     |
| dk      | 4,3 | 5,5 | 6,8 | 7,5 |
| k       | 1,3 | 1,7 | 2,1 | 2,3 |
| m       | 2,4 | 2,8 | 4   | 4,2 |
| Antrieb | PZ1 | PZ1 | PZ2 | PZ2 |

DIN 7982 A4 PZ  
Senk-Blechschauben mit Kreuzschlitz

DIN 7982 A4 PZ  
Cross recessed countersunk head tapping screws

DIN 7982  
A4  
Alternative Norm  
ersetzt durch ISO 7050

| d    | 4,2                 | 4,8                 | 5,5                 | 6,3                 |
|------|---------------------|---------------------|---------------------|---------------------|
| l/mm | Art. Nr. / Item no. | Art. Nr. / Item no. | Art. Nr. / Item no. | Art. Nr. / Item no. |
| 4,5  |                     |                     |                     |                     |
| 6,5  |                     |                     |                     |                     |
| 9,5  | 79824042 95         | 79824048 95         |                     |                     |
| 13   | 79824042 13         | 79824048 13         | 79824055 13         | 79824063 13         |
| 16   | 79824042 16         | 79824048 16         | 79824055 16         | 79824063 16         |
| 19   | 79824042 19         | 79824048 19         | 79824055 19         | 79824063 19         |
| 22   | 79824042 22         | 79824048 22         | 79824055 22         | 79824063 22         |
| 25   | 79824042 25         | 79824048 25         | 79824055 25         | 79824063 25         |
| 28   |                     |                     |                     |                     |
| 32   | 79824042 32         | 79824048 32         | 79824055 32         | 79824063 32         |
| 35   |                     | 79824048 35         |                     |                     |
| 38   | 79824042 38         | 79824048 38         | 79824055 38         | 79824063 38         |
| 42   |                     |                     | 79824055 42         |                     |
| 45   | 79824042 45         | 79824048 45         | 79824055 45         | 79824063 45         |
| 50   | 79824042 50         | 79824048 50         | 79824055 50         | 79824063 50         |
| 55   |                     | 79824048 55         | 79824055 55         |                     |
| 60   | 79824042 60         | 79824048 60         | 79824055 60         | 79824063 60         |
| 70   | 79824042 70         | 79824048 70         | 79824055 70         | 79824063 70         |
| 80   | 79824042 80         | 79824048 80         | 79824055 80         | 79824063 80         |
| 90   |                     | 79824048 90         | 79824055 90         | 79824063 90         |
| 100  | 79824042 100        | 79824048 100        | 79824055 100        | 79824063 100        |
| 110  |                     | 79824048 110        |                     |                     |
| 120  |                     | 79824048 120        | 79824055 120        | 79824063 120        |



TX Form siehe ISO 14586  
- Blechgewinde  
- PZ  
- Senkkopf

TX type see ISO 14586  
- Sheet thread  
- PZ  
- Countersunk head

|         |     |     |      |      |
|---------|-----|-----|------|------|
|         |     |     |      |      |
| dk      | 8,1 | 9,5 | 10,8 | 12,4 |
| k       | 2,5 | 3   | 3,4  | 3,8  |
| m       | 4,4 | 5   | 6,3  | 7    |
| Antrieb | PZ2 | PZ2 | PZ3  | PZ3  |

DIN