


COLLIER DE SERRAGE BANDE NON PERFOREE DE 5 MM, 9 MM OU 12 MM

WORM DRIVE HOSE CLIPS NON PERFORATED BAND 5, 9 OR 12MM

SCHNECKENGEWINDESCHELLEN GEPRÄGTES BAND 5, 9 ODER 12MM

ABRAZADERA SIN FIN, CINTA NO PERFORADA DE 5, 9 O 12MM



d	Code	s	e	l	Cond.	Sur-cond.	kg/100	€/100
7-11	NP5 7-11	4	0,4	5,10	100	2000	0,355	48,23
10-19	NP5 10-19	4	0,4	5,10	100	2000	0,380	48,23
8-12	NP9 8-12	7	0,83	9,15	50	1000	1,150	36,33
10-16	NP9 10-16	7	0,83	9,15	50	1000	1,300	36,39
12-22	NP9 12-22	7	0,83	9,15	50	1000	1,400	39,37
16-27	NP9 16-27	7	0,83	9,15	50	1000	1,500	41,73
20-32	NP9 20-32	7	0,83	9,15	50	1000	1,600	45,82
25-40	NP9 25-40	7	0,83	9,15	25	500	1,800	52,39
30-45	NP9 30-45	7	0,83	9,15	25	500	1,900	54,69
32-50	NP9 32-50	7	0,83	9,15	25	500	2,000	55,99
40-60	NP9 40-60	7	0,83	9,15	25	500	2,200	61,69
50-70	NP9 50-70	7	0,83	9,15	20	400	2,400	69,00
60-80	NP9 60-80	7	0,83	9,15	20	400	2,600	70,85
70-90	NP9 70-90	7	0,83	9,15	10	200	2,700	73,22
80-100	NP9 80-100	7	0,83	9,15	10	200	3,000	74,34
90-110	NP9 90-110	7	0,83	9,15	10	200	3,100	73,35
100-120	NP9 100-120	7	0,83	9,15	10	200	3,300	76,19
110-130	NP9 110-130	7	0,83	9,15	10	200	3,500	80,85
120-140	NP9 120-140	7	0,83	9,15	10	200	3,700	87,91
16-27	NP12 16-27	7	0,83	12,15	25	500	2,000	52,82
20-32	NP12 20-32	7	0,83	12,15	25	500	2,200	54,25
25-40	NP12 25-40	7	0,83	12,15	25	500	2,400	59,26
30-45	NP12 30-45	7	0,83	12,15	25	500	2,500	63,98
32-50	NP12 32-50	7	0,83	12,15	25	500	2,600	64,35
40-60	NP12 40-60	7	0,83	12,15	10	200	2,700	67,27
50-70	NP12 50-70	7	0,83	12,15	10	200	2,900	72,29
60-80	NP12 60-80	7	0,83	12,15	10	200	3,100	77,81
70-90	NP12 70-90	7	0,83	12,15	10	200	3,300	79,72
80-100	NP12 80-100	7	0,83	12,15	10	200	3,500	86,60
90-110	NP12 90-110	7	0,83	12,15	10	200	3,800	89,15
100-120	NP12 100-120	7	0,83	12,15	10	200	4,400	93,25
110-130	NP12 110-130	7	0,83	12,15	10	200	4,500	97,84
120-140	NP12 120-140	7	0,83	12,15	10	200	4,700	96,59
130-150	NP12 130-150	7	0,83	12,15	10	100	5,000	112,77
140-160	NP12 140-160	7	0,83	12,15	10	100	5,200	115,14
150-170	NP12 150-170	7	0,83	12,15	10	100	5,400	117,62
160-180	NP12 160-180	7	0,83	12,15	10	100	5,600	119,78
170-190	NP12 170-190	7	0,83	12,15	10	100	5,800	123,23
180-200	NP12 180-200	7	0,83	12,15	10	100	6,100	128,95
190-210	NP12 190-210	7	0,83	12,15	10	100	6,400	139,05
200-220	NP12 200-220	7	0,83	12,15	10	100	6,700	163,66



Couple de serrage recommandé / recommended torque :
5 mm = 0,8Nm ; 9 mm = 3Nm ; 12 mm = 4,5Nm