




Vis universelle, Tête ronde,

Cruciforme Z, filetage total

4CUT

Trempé, avec revêtement anti-friction




Ø du filetage d1	Dimensions [mm]			Unités d'emballage SPAX Box [Pièces]	Code article SPAX	Code EAN
	Longueur totale Ls	Longueur filetage totale Lg	Taille de l'embout Z			
Conditionnement standard						
3,0* Ø d _k = 6,0 mm	10	8	1	1.000	0231010300105	4003530014970
	12	11	1	1.000	0231010300125	4003530014987
	15	13	1	1.000	0231010300155	4003530015007
	16	15	1	1.000	0231010300165	4003530015014
	20	18	1	1.000	0231010300205	4003530015038
	25	23	1	1.000	0231010300255	4003530015045
30	28	1	1.000	0231010300305	4003530015052	
3,5 Ø d _k = 7,0 mm	12	11	2	1.000	0231010350125	4003530015069
	15	13	2	1.000	0231010350155	4003530015083
	16	15	2	1.000	0231010350165	4003530015090
	20	18	2	1.000	0231010350205	4003530015106
	25	23	2	1.000	0231010350255	4003530015113
	30	27	2	1.000	0231010350305	4003530015120
	35	32	2	1.000	0231010350355	4003530015137
40	37	2	1.000	0231010350405	4003530015144	
4,0 Ø d _k = 8,0 mm	12	11	2	1.000	0231010400125	4003530015151
	15	13	2	1.000	0231010400155	4003530015175
	16	15	2	1.000	0231010400165	4003530015182
	20	18	2	1.000	0231010400205	4003530015212
	25	23	2	1.000	0231010400255	4003530015229
	30	27	2	1.000	0231010400305	4003530015236
	35	32	2	1.000	0231010400355	4003530015243
	40	37	2	500	0231010400405	4003530015250
	45	42	2	500	0231010400455	4003530015267
	50	47	2	500	0231010400505	4003530015274
60	50**	2	500	0231010400605	4003530015281	
4,5 Ø d _k = 9,0 mm	12	11	2	1.000	0231010450125	4003530015298
	15	13	2	1.000	0231010450155	4003530015304
	16	15	2	1.000	0231010450165	4003530015311

*Autres conceptions sur demande.

**Autres conceptions sur demande. Le filetage ne va pas complètement jusqu'à la tête.





Vis universelle, Tête ronde,
Cruciforme Z, filetage total

4CUT

Trempé, avec revêtement anti-friction



A9J

Ø du filetage d1	Dimensions [mm]			Unités d'emballage SPAX Box [Pièces]	Code article SPAX	Code EAN
	Longueur totale Ls	Longueur filetage totale Lg	Taille de l'embout Z			
Conditionnement standard						
4,5 Ø dk = 9,0 mm	20	17	2	1.000	0231010450205	4003530015335
	25	22	2	1.000	0231010450255	4003530015342
	30	27	2	500	0231010450305	4003530015359
	35	32	2	500	0231010450355	4003530015366
	40	37	2	500	0231010450405	4003530015373
	45	42	2	500	0231010450455	4003530015380
	50	47	2	500	0231010450505	4003530015397
	60	57	2	500	0231010450605	4003530103353
5,0 Ø dk = 9,9 mm	15	12	2	1.000	0231010500155	4003530039478
	16	14	2	1.000	0231010500165	4003530015403
	20	17	2	1.000	0231010500205	4003530015427
	25	22	2	500	0231010500255	4003530015434
	30	27	2	500	0231010500305	4003530015441
	35	32	2	500	0231010500355	4003530015458
	40	37	2	500	0231010500405	4003530016059
	45	41	2	200	0231010500455	4003530015472
	50	46	2	200	0231010500505	4003530015489
	60	56	2	200	0231010500605	4003530015496
	70	61*	2	200	0231010500705	4003530015502
	80	61*	2	200	0231010500805	4003530015519
	90	61*	2	200	0231010500905	4003530015526
6,0 Ø dk = 11,6 mm	20	17	3	500	0231010600205	4003530103414
	25	22	3	500	0231010600255	4003530103421
	30	27	3	500	0231010600305	4003530015533
	35	32	3	500	0231010600355	4003530015540
	40	37	3	500	0231010600405	4003530015557
	50	46	3	200	0231010600505	4003530015571
	60	56	3	200	0231010600605	4003530015588
	70	61*	3	200	0231010600705	4003530015595
	80	61*	3	200	0231010600805	4003530015601
	90	61*	3	200	0231010600905	4003530015618
	100	61*	3	100	0231010601005	4003530015625

*Autres conceptions sur demande. Le filetage ne va pas complètement jusqu'à la tête.

Produit susceptible d'être modifié

