

Acier Zn

33 361


DIN 7504 M - (similar ISO 15481)

## VIS AUTOPERCEUSES TETE CYLINDRIQUE CRANTEE EMPREINTE CARREE

SELF DRILLING SCREWS PAN HEAD SQUARE RECESS WITH SERRATION

LINSENBOHRSCHRAUBEN MIT VIERKANTSCHLITZ UND UNTERKOPFVERZÄHNING

TORNILLOS AUTOTALADRANTES CABEZA CILINDRICA CON MUESCAS Y HUECO CUADRADO



d	3,5 (6)	3,9 (7)	4,2 (8)	4,8 (10)	5,5 (12)
d2	6,9	7,5	8,2	9,5	10,8
k	2,6	2,8	3,05	3,55	3,95
⌀	1	2	2	2	3
Capacité de perçage	2,25	2,4	3	4,4	5,25

d x L	Code	Cond.	Sur-cond.	kg/100
3,5X9,5	333613,5X9,5CR3	500	19000	0,104
3,5X13	333613,5X13CR3	500	19000	0,119
3,5X16	333613,5X16CR3	500	9000	0,132
3,5X19	333613,5X19CR3	500	9000	0,144
3,5X25	333613,5X25CR3	500	9000	0,170
3,9X9,5	333613,9X9,5CR3	500	19000	0,108
3,9X13	333613,9X13CR3	500	9000	0,128
3,9X16	333613,9X16CR3	500	9000	0,148
3,9X19	333613,9X19CR3	500	9000	0,167
3,9X25	333613,9X25CR3	500	4000	0,205
3,9X32	333613,9X32CR3	500	4000	0,228
3,9X38	333613,9X38CR3	500	4000	0,260
4,2X13	333614,2X13CR3	500	9000	0,150
4,2X16	333614,2X16CR3	500	9000	0,201
4,2X16**	333614,2X16CR3TB+EMB	500	9000	0,201
4,2X19	333614,2X19CR3	500	9000	0,190
4,2X19**	333614,2X19CR3TB+EMB	500	9000	0,190
4,2X25	333614,2X25CR3	500	4000	0,257
4,2X32	333614,2X32CR3	500	4000	0,263
4,2X38	333614,2X38CR3	500	4000	0,339
4,2X45	333614,2X45CR3	500	2000	0,388

d x L	Code	Cond.	Sur-cond.	kg/100
4,2X50	333614,2X50CR3	500	2000	0,414
4,2X60	333614,2X60CR3	500	2000	0,476
4,8X13	333614,8X13CR3	500	9000	0,285
4,8X16	333614,8X16CR3	500	4000	0,310
4,8X19	333614,8X19CR3	500	4000	0,335
4,8X25	333614,8X25CR3	250	4500	0,384
4,8X32	333614,8X32CR3	250	2000	0,408
4,8X38	333614,8X38CR3	250	2000	0,491
4,8X45	333614,8X45CR3	250	2000	0,548
4,8X50	333614,8X50CR3	250	2000	0,589
4,8X60	333614,8X60CR3	250	1000	0,671
4,8X70	333614,8X70CR3	250	1000	0,754
4,8X80	333614,8X80CR3	250	500	0,836
5,5X19	333615,5X19CR3	250	4500	0,456
5,5X22	333615,5X22CR3	250	4500	0,489
5,5X25	333615,5X25CR3	250	2000	0,521
5,5X32	333615,5X32CR3	250	2000	0,480
5,5X38	333615,5X38CR3	250	1000	0,580
5,5X45	333615,5X45CR3	250	1000	0,660
5,5X50	333615,5X50CR3	250	1000	0,731