

W1


NP
DIN 3017

COLLIER DE SERRAGE BANDE NON PERFOREE DE 5 MM, 9 MM OU 12 MM

WORM DRIVE HOSE CLIPS NON PERFORATED BAND 5, 9 OR 12MM

SCHNECKENGEWINDESCHELLEN GEPRÄGTES BAND 5, 9 ODER 12MM

ABRAZADERA SIN FIN, CINTA NO PERFORADA DE 5, 9 O 12MM



d	Code	s	e	l	Cond.	Sur-cond.	kg/100
7-11	NP5 7-11	4	0,4	5,10	100	2000	0,355
10-19	NP5 10-19	4	0,4	5,10	100	2000	0,380
8-12	NP9 8-12	7	0,83	9,15	50	1000	1,150
10-16	NP9 10-16	7	0,83	9,15	50	1000	1,300
12-22	NP9 12-22	7	0,83	9,15	50	1000	1,400
16-27	NP9 16-27	7	0,83	9,15	50	1000	1,500
20-32	NP9 20-32	7	0,83	9,15	50	1000	1,600
25-40	NP9 25-40	7	0,83	9,15	25	500	1,800
30-45	NP9 30-45	7	0,83	9,15	25	500	1,900
32-50	NP9 32-50	7	0,83	9,15	25	500	2,000
40-60	NP9 40-60	7	0,83	9,15	25	500	2,200
50-70	NP9 50-70	7	0,83	9,15	20	400	2,400
60-80	NP9 60-80	7	0,83	9,15	20	400	2,600
70-90	NP9 70-90	7	0,83	9,15	10	200	2,700
80-100	NP9 80-100	7	0,83	9,15	10	200	3,000
90-110	NP9 90-110	7	0,83	9,15	10	200	3,100
100-120	NP9 100-120	7	0,83	9,15	10	200	3,300
110-130	NP9 110-130	7	0,83	9,15	10	200	3,500
120-140	NP9 120-140	7	0,83	9,15	10	200	3,700
16-27	NP12 16-27	7	0,83	12,15	25	500	2,000
20-32	NP12 20-32	7	0,83	12,15	25	500	2,200
25-40	NP12 25-40	7	0,83	12,15	25	500	2,400
30-45	NP12 30-45	7	0,83	12,15	25	500	2,500
32-50	NP12 32-50	7	0,83	12,15	25	500	2,600
40-60	NP12 40-60	7	0,83	12,15	10	200	2,700
50-70	NP12 50-70	7	0,83	12,15	10	200	2,900
60-80	NP12 60-80	7	0,83	12,15	10	200	3,100
70-90	NP12 70-90	7	0,83	12,15	10	200	3,300
80-100	NP12 80-100	7	0,83	12,15	10	200	3,500
90-110	NP12 90-110	7	0,83	12,15	10	200	3,800
100-120	NP12 100-120	7	0,83	12,15	10	200	4,400
110-130	NP12 110-130	7	0,83	12,15	10	200	4,500
120-140	NP12 120-140	7	0,83	12,15	10	200	4,700
130-150	NP12 130-150	7	0,83	12,15	10	100	5,000
140-160	NP12 140-160	7	0,83	12,15	10	100	5,200
150-170	NP12 150-170	7	0,83	12,15	10	100	5,400
160-180	NP12 160-180	7	0,83	12,15	10	100	5,600
170-190	NP12 170-190	7	0,83	12,15	10	100	5,800
180-200	NP12 180-200	7	0,83	12,15	10	100	6,100
190-210	NP12 190-210	7	0,83	12,15	10	100	6,400
200-220	NP12 200-220	7	0,83	12,15	10	100	6,700



Couple de serrage recommandé / recommended torque :
5 mm = 0.8Nm ; 9 mm = 3Nm ; 12 mm = 4.5Nm