


W5

NPSSM

DIN 3017

COLLIER DE SERRAGE BANDE NON PERFOREE DE 9 MM OU 12 MM

WORM DRIVE HOSE CLIPS NON PERFORATED BAND 9 OR 12MM
SCHNECKENGEWINDESCHELLEN GEPRÄGTES BAND 9 ODER 12MM
ABRAZADERA SIN FIN, CINTA NO PERFORADA DE 9 O 12MM



| d | Code | s | e | l | Cond. | Sur-cond. | kg/100 | €/100 |
|---------|-----------------|---|------|-------|-------|-----------|--------|--------|
| 8-12 | NPSSM9 8-12 | 7 | 0,73 | 9,15 | 50 | 1000 | 1,200 | 135,34 |
| 10-16 | NPSSM9 10-16 | 7 | 0,73 | 9,15 | 50 | 1000 | 1,300 | 135,34 |
| 12-22 | NPSSM9 12-22 | 7 | 0,73 | 9,15 | 50 | 1000 | 1,400 | 139,75 |
| 16-27 | NPSSM9 16-27 | 7 | 0,73 | 9,15 | 50 | 1000 | 1,500 | 152,76 |
| 20-32 | NPSSM9 20-32 | 7 | 0,73 | 9,15 | 50 | 1000 | 1,600 | 165,03 |
| 25-40 | NPSSM9 25-40 | 7 | 0,73 | 9,15 | 25 | 500 | 1,700 | 179,80 |
| 30-45 | NPSSM9 30-45 | 7 | 0,73 | 9,15 | 25 | 500 | 1,800 | 185,00 |
| 32-50 | NPSSM9 32-50 | 7 | 0,73 | 9,15 | 25 | 500 | 1,900 | 189,82 |
| 40-60 | NPSSM9 40-60 | 7 | 0,73 | 9,15 | 25 | 500 | 2,000 | 202,74 |
| 50-70 | NPSSM9 50-70 | 7 | 0,73 | 9,15 | 20 | 400 | 2,100 | 216,51 |
| 60-80 | NPSSM9 60-80 | 7 | 0,73 | 9,15 | 20 | 400 | 2,300 | 232,62 |
| 70-90 | NPSSM9 70-90 | 7 | 0,73 | 9,15 | 10 | 200 | 2,400 | 238,56 |
| 80-100 | NPSSM9 80-100 | 7 | 0,73 | 9,15 | 10 | 200 | 2,500 | 244,83 |
| 90-110 | NPSSM9 90-110 | 7 | 0,73 | 9,15 | 10 | 200 | 2,700 | 257,41 |
| 16-27 | NPSSM12 16-27 | 7 | 0,73 | 12,15 | 25 | 500 | 1,800 | 193,00 |
| 20-32 | NPSSM12 20-32 | 7 | 0,73 | 12,15 | 25 | 500 | 1,900 | 201,86 |
| 25-40 | NPSSM12 25-40 | 7 | 0,73 | 12,15 | 25 | 500 | 2,000 | 218,91 |
| 30-45 | NPSSM12 30-45 | 7 | 0,73 | 12,15 | 25 | 500 | 2,000 | 234,77 |
| 32-50 | NPSSM12 32-50 | 7 | 0,73 | 12,15 | 25 | 500 | 2,200 | 236,84 |
| 40-60 | NPSSM12 40-60 | 7 | 0,73 | 12,15 | 10 | 200 | 2,500 | 244,65 |
| 50-70 | NPSSM12 50-70 | 7 | 0,73 | 12,15 | 10 | 200 | 2,700 | 264,05 |
| 60-80 | NPSSM12 60-80 | 7 | 0,73 | 12,15 | 10 | 200 | 3,000 | 287,29 |
| 70-90 | NPSSM12 70-90 | 7 | 0,73 | 12,15 | 10 | 200 | 3,200 | 298,33 |
| 80-100 | NPSSM12 80-100 | 7 | 0,73 | 12,15 | 10 | 200 | 3,400 | 303,53 |
| 90-110 | NPSSM12 90-110 | 7 | 0,73 | 12,15 | 10 | 200 | 3,700 | 310,11 |
| 100-120 | NPSSM12 100-120 | 7 | 0,73 | 12,15 | 10 | 200 | 3,900 | 324,50 |
| 110-130 | NPSSM12 110-130 | 7 | 0,73 | 12,15 | 10 | 200 | 4,100 | 335,52 |
| 120-140 | NPSSM12 120-140 | 7 | 0,73 | 12,15 | 10 | 200 | 4,400 | 357,23 |
| 130-150 | NPSSM12 130-150 | 7 | 0,73 | 12,15 | 10 | 100 | 4,600 | 370,19 |
| 140-160 | NPSSM12 140-160 | 7 | 0,73 | 12,15 | 10 | 100 | 4,800 | 387,42 |
| 150-170 | NPSSM12 150-170 | 7 | 0,73 | 12,15 | 10 | 100 | 5,000 | 382,59 |
| 160-180 | NPSSM12 160-180 | 7 | 0,73 | 12,15 | 10 | 100 | 5,200 | 389,34 |
| 170-190 | NPSSM12 170-190 | 7 | 0,73 | 12,15 | 10 | 100 | 5,400 | 433,72 |
| 180-200 | NPSSM12 180-200 | 7 | 0,73 | 12,15 | 10 | 100 | 5,600 | 485,73 |



Couple de serrage recommandé / recommended torque :
9 mm = 4Nm ; 12 mm = 5.5Nm