



Anti-tamper cap valve G $\frac{3}{4}$ x G $\frac{3}{4}$

Part no. 77949

anti-tamper cap valves

benefits

- integrated boiler filling and drain valve KFE for easy draining of the expansion vessel
- high draining capacity for easy and fast draining
- with shut-off valve which can be secured against inadvertent closing by means of a lead seal

Application

For connection, maintenance and checks of diaphragm expansion vessels in heating systems as per EN 12828 and in solar systems. To be installed at the water inlet of the expansion vessel.

Description

Anti-tamper cap valve with screw connection G $\frac{3}{4}$ x G $\frac{3}{4}$ or G1 x G1. The shut-off valve is secured against inadvertent closing by means of a cap and a lead seal. The integrated boiler filling and drain valve KFE (connection: G $\frac{3}{4}$ eurocone) allows for easy draining of the expansion vessel. For this purpose, a hose can be connected by means of a union nut. The expansion vessel can be shut off from the heating system and drained with a high draining capacity (time saving) via the drain valve for the required function check or for replacement.

Technical Specifications

Operating pressure

max. 10 bar

Operating temperature range

Medium: 0/120 °C

Connections

Inlet x outlet: x G $\frac{3}{4}$

Boiler filling and drain valve KFE: G $\frac{3}{4}$ male eurocone

Drain capacity

anti-tamper cap valve with boiler filling and drain valve KFE
1.5 m³/h

Versions

			Part no.
Anti-tamper cap valve G ³ / ₄ x G ³ / ₄	with integrated boiler filling and drain valve KFE G ³ / ₄		77949

-  in-stock items
-  Non-stock items