



bimetal thermometer BiTh 63 Ch

Part no. 66610402

bimetal thermometer

benefits

- ideal for hygienic processes
- accuracy class 1 as per EN 13190
- for temperatures of the medium of up to 160 °C
- Process connection centre back or bottom or threads various thermowells

Application


For corrosive media. Meets high measuring demands, e.g. in process engineering as well as chemical and food industry applications.

Options

- Thermowell G $\frac{1}{2}$ B, stainless steel 316 Ti/316 L
- Grooved nut connection as per DIN 11851
- other connection designs
- other ranges
- other stem lengths
- laminated safety glass window
- Glycerine filling
- Every angle version
- back flange
- 3-hole fixing, panel mounting bezel
- special materials

Technical Drawings

bottom connection, plain



Dimensions (mm)

NG	a2	b4	D	l2
63	15,5	45	63	67
63	15,5	45	63	104
63	15,5	45	63	154
63	15,5	45	63	204
100	17,5	49,5	100	67
100	17,5	49,5	100	104
100	17,5	49,5	100	154
100	17,5	49,5	100	204
160	15,5	48	160	67
160	15,5	48	160	104
160	15,5	48	160	154
160	15,5	48	160	204

Versions

Type	housing ø	mounting position	Range	For thermowell with length L1	Type	Type	Part no.
BiTh 63 Ch	63 mm	bottom	-20/+60 °C	200 mm	BiTh 63 Ch	D402	66610402

- in-stock items
- Non-stock items