



Boiler manifolds for heating pump assemblies Primo-Therm®

benefits

- compact and robust version in form-fit insulation
- for two or three heating pump assemblies, with optional hydraulic separator
- 2 wall mounting bracket for easy mounting included
- AFRISO boiler manifolds are tightness-tested in the factory.



Application

For distribution of the heating circuit water in sealed heating systems as per EN 12828 from the boiler to the heating pump assemblies Primo-Therm®.

Description

Boiler manifold as combination flow and return manifold for two, three, four or five heating pump assemblies. AFRISO boiler manifolds are tightness-tested in the factory; they are maintenance-free.

Technical Specifications

system connections

160 kW
threaded socket G2 male
160 kW
union nut G1½, flat-sealing

Axis distance

125 mm

Operating temperature range

Medium: max. 110 °C

Flow

160 kW
7 m³/h

System pressure

max. 6 bar

Heat insulation

Polypropylene EPP

Scope of delivery

- Boiler manifold
- 2 x wall mounting bracket
- Insulation

Versions

	Heating circuits	hydraulic separator		Part no.
Boiler manifold KSV 125-2 160 kW	2	0		77319
Boiler manifold KSV 125-3 160 kW	3	0		77320
Boiler manifold KSV 125-4 160 kW	4	0		77321
Boiler manifold KSV 125-5 160 kW	5	0		77322

 in-stock items

 Non-stock items