



## Boiler manifold KSV 125-5 160 kW

Part no. 77322

Boiler manifolds for heating pump assemblies Primo-Therm®

### benefits

- compact and robust version in form-fit insulation
- for two or three heating pump assemblies, with optional hydraulic separator
- 2 wall mounting bracket for easy mounting included
- AFRISO boiler manifolds are tightness-tested in the factory.

### Application

For distribution of the heating circuit water in sealed heating systems as per EN 12828 from the boiler to the heating pump assemblies Primo-Therm®.

### Description

Boiler manifold as combination flow and return manifold for two, three, four or five heating pump assemblies. AFRISO boiler manifolds are tightness-tested in the factory; they are maintenance-free.

### Technical Specifications

#### system connections

160 kW  
threaded socket G2 male  
160 kW  
union nut G1½, flat-sealing

#### Axis distance

125 mm

#### Operating temperature range

Medium: max. 110 °C

#### Flow

160 kW  
7 m³/h

#### System pressure

max. 6 bar

#### Heat insulation

Polypropylene EPP

#### Scope of delivery

- Boiler manifold
- 2 x wall mounting bracket
- Insulation

Versions

|                                        | Heating circuits | hydraulic separator |                                                                                     | Part no. |
|----------------------------------------|------------------|---------------------|-------------------------------------------------------------------------------------|----------|
| Boiler manifold<br>KSV 125-5<br>160 kW | 5                | 0                   |  | 77322    |

-  in-stock items
-  Non-stock items