



Bourdon tube pressure gauges for heating/plumbing applications

benefits

- with self-sealing connection thread (NG 50 and 63) for fast mounting
- red maximum mark on dial
- adjustable red reference pointer and green operation segment on window
- corrosion-resistant housing

Application

For gaseous and liquid media which are not highly viscous, do not crystallise and do not attack copper alloys and EPDM.

! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

Technical Specifications

Nominal size

63

accuracy class (EN 837-1/6)

2.5

application area

static load: $\frac{3}{4}$ x full scale value

dynamic load: $\frac{2}{3}$ x full scale value

short-term: Full scale value

Operating temperature range

Medium: max. 60 °C

Ambient: -20/+60 °C

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:

at rising temperature approx. $\pm 0.4 \text{ } \%/10 \text{ K}$

falling temperature approx. $\pm 0.4 \text{ } \%/10 \text{ K}$

of full scale value

Degree of protection

IP 32 (EN 60529)

Connection

Brass, bottom

NG 63

G $\frac{1}{2}$ B, Self-sealing with PTFE sealing ring

Measuring element

Bourdon tube, "C" type tube

Copper alloy

movement

Brass

Dial

Plastic, white

Scaling: black


Pointer

Plastic, black

Housing
Plastic (ABS), black, highly impact-resistant and corrosion-resistant

window
Plastic, clipped in
with adjustable red reference pointer and green flag

Technical Drawings



Versions

	housing ø	Conne- ction	Conne- ction	Thread	alignment	Range	Type		Part no.
HZ 63	63 mm	G $\frac{3}{8}$ B		Self-sea- ling with PTFE sealing ring	bottom	0/4 bar	HZ 63 rad	●	63908
HZ 63	63 mm	G $\frac{3}{8}$ B		Self-sea- ling with PTFE sealing ring	bottom	0/4 bar	HZ 63 rad	●	63910

- in-stock items
- Non-stock items