




Bourdon tube pressure gauges for ultra-pure gas applications type D3

benefits

- wetted parts specially cleaned, flushed and electropolished
- tightness-tested with helium
- rear blow-out
- versatile connection technology
- GOSSTANDART-certified

Application

Designed for highly demanding applications in terms of surface quality and purity of the wetted parts, particularly for measuring ultra-pure gases.
! For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

Technical Specifications

Type

D3

Nominal size

63

accuracy class (EN 837-1/6)

1.6

ranges (EN 837-1/5)

see ordering table

Calibration medium

Nitrogen or dried air

application area

static load: $\frac{3}{4}$ x full scale value
dynamic load: $\frac{2}{3}$ x full scale value
short-term: Full scale value

Operating temperature range

Medium: max. 150 °C

Ambient: -20/+60 °C

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:
at rising temperature approx. ± 0.4 %/10 K
falling temperature approx. ± 0.4 %/10 K
of full scale value

Degree of protection

IP 32 (EN 60529)

Connection

stainless steel 316 Ti/316 L, bottom
9/16-18 UNF, with union nut

Measuring element

Bourdon tube, stainless steel 316 Ti/316 L
 ≤ 60 bar: "C" type tube
 > 60 bar: helical tube
 tightness-tested with helium,
 leak rate $\leq 10^{-9}$ mbar x l/s

wetted parts

Connection, Measuring element
 stainless steel 316 Ti/316 L
 cleaned, flushed with nitrogen, electropolished, surface roughness
 $\leq R_a 0.6 \mu\text{m}$

movement

Stainless steel

Dial

Aluminium, white
 Scaling: black
 label: ultra-pure gas

Pointer

Aluminium, black

Housing

Stainless steel 304, with rear blow-out

push on bezel

Stainless steel 304, bare metal surface

window


Plastic

Options

- surface roughness $R_a 0.4 \mu\text{m}$
- Housing polished
- Push on bezel polished
- Electrical contacts
- NG 50
- special scales
- other process connections

Technical Drawings

Bottom connection, 9/16-18 UNF, with union nut



Union nut

Dimensions (mm)

NG	a	b	D	D1	h1	s
63	9	28	63	62	57	8

Versions

Range	Mounting type	Type		Part number
-1/+0 bar	direct	RF63RG D302	●	87101302
-1/+0.6 bar	direct	RF63RG D302	●	87102302
-1/+1.5 bar	direct	RF63RG D302	●	87103302
-1/+3 bar	direct	RF63RG D302	●	87104302
-1/+5 bar	direct	RF63RG D302	●	87105302
-1/+9 bar	direct	RF63RG D302	●	87106302
-1/+15 bar	direct	RF63RG D302	●	87107302
0/0.6 bar	direct	RF63RG D302	●	87109302
0/1 bar	direct	RF63RG D302	●	87110302
0/1.6 bar	direct	RF63RG D302	●	87111302
0/2.5 bar	direct	RF63RG D302	●	87112302
0/4 bar	direct	RF63RG D302	●	87113302
0/6 bar	direct	RF63RG D302	●	87114302
0/10 bar	direct	RF63RG D302	●	87115302
0/16 bar	direct	RF63RG D302	●	87116302
0/25 bar	direct	RF63RG D302	●	87117302
0/40 bar	direct	RF63RG D302	●	87118302
0/60 bar	direct	RF63RG D302	●	87119302

0/100 bar	direct	RF63RG D302	●	87120302
0/160 bar	direct	RF63RG D302	●	87121302
0/250 bar	direct	RF63RG D302	●	87122302
0/400 bar	direct	RF63RG D302	●	87123302

● in-stock items

● Non-stock items