



Bourdon tube pressure gauge for high pressures type D4

benefits

- for pressure ranges up to 4,000 bar
- Housing with solid baffle wall and blow-out

Application

For measurement of extremely high pressures in gaseous and liquid corrosive media which are not highly viscous and do not crystallise; also suitable for corrosive atmospheres.

Technical Specifications

Type
D4

Nominal size
160

accuracy class (EN 837-1/6)
1.0

Operating temperature range
Medium: max. 100 °C
Ambient: -20/+60 °C

Temperature performance
Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:
at rising temperature approx. $\pm 0.4 \text{ } \%/10 \text{ K}$
falling temperature approx. $\pm 0.4 \text{ } \%/10 \text{ K}$
of full scale value

Connection
Stainless steel 316 L, bottom
HP connection $\frac{1}{4}$ " with female thread M16 x 1.5 with sealing cone 60°

Measuring element
Bourdon tube, NiFe alloy

movement
Stainless steel

Dial
Aluminium, white
Scaling: black

Pointer
Aluminium, black

Housing
Stainless steel 304, with solid baffle wall and blow-out



bayonet bezel
Stainless steel 304

window
Laminated safety glass

Options

- Glycerine filling (type D802)
- 3-hole fixing, panel mounting bezel
- HP connection male thread 9/16-18 UNF-2A-LH with sealing cone 60°
- other process connections

Technical Drawings



Versions

Range	Mounting type	Type	Part number
0/2500 bar	direct	RF160HD D402	85277402
0/4000 bar	direct	RF160HD D402	85278402

- in-stock items
- Non-stock items