



Bourdon tube pressure gauges for industrial applications type D2

benefits

- for machine and plant engineering
- robust steel housing
- many customised versions available

Application

For gaseous and liquid media which are not highly viscous, do not crystallise and do not attack copper alloys.

! For high measuring accuracy. For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

Technical Specifications

Type

D2

Nominal size

100

accuracy class (EN 837-1/6)

1.0

ranges (EN 837-1/5)

see ordering table

application area

≤ 600 bar: Full scale value
 > 600 bar: $\frac{3}{4}$ x full scale value
 ≤ 600 bar: 0.9 x full scale value
 > 600 bar: $\frac{2}{3}$ x full scale value
 ≤ 600 bar: 1.3 x full scale value
 > 600 bar: Full scale value

Operating temperature range

Medium: max. 60 °C

Ambient: -20/+60 °C

Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:

at rising temperature approx. $\pm 0.4 \text{ } \%/10 \text{ K}$

falling temperature approx. $\pm 0.4 \text{ } \%/10 \text{ K}$

of full scale value

Degree of protection

IP 32 (EN 60529)

Connection

Brass, bottom

Measuring element

Bourdon tube

≤ 60 bar: "C" type tube, Copper alloy

> 60 bar: helical tube, stainless steel 316 Ti/316 L

movement
Brass

Dial
Aluminium, white
Scaling: black

Pointer
Aluminium, black

Housing
Sheet steel, black


window
Plastic, clipped in

Options

- throttle screw
- Reference pointer
- Electrical contacts
- special scales
- other process connections

Technical Drawings

Bottom connection



Dimensions (mm)

NG	a	b	øc	c1	c2	G	h	s	SW
100	15,6	44	6	3	20	G½B	86	3,5	22

Versions

Range	Mounting type	Type		Part number
-1/+0 bar	direct	RF100I D201	●	85301201
-1/+0.6 bar	direct	RF100I D201	●	85302201
-1/+1.5 bar	direct	RF100I D201	●	85303201
-1/+3 bar	direct	RF100I D201	●	85304201
-1/+5 bar	direct	RF100I D201	●	85305201
-1/+9 bar	direct	RF100I D201	●	85306201
-1/+15 bar	direct	RF100I D201	●	85307201
0/0.6 bar	direct	RF100I D201	●	85309201
0/1 bar	direct	RF100I D201	●	85310201
0/1.6 bar	direct	RF100I D201	●	85311201
0/2.5 bar	direct	RF100I D201	●	85312201
0/4 bar	direct	RF100I D201	●	85313201
0/6 bar	direct	RF100I D201	●	85314201
0/10 bar	direct	RF100I D201	●	85315201
0/16 bar	direct	RF100I D201	●	85316201
0/25 bar	direct	RF100I D201	●	85317201
0/40 bar	direct	RF100I D201	●	85318201
0/60 bar	direct	RF100I D201	●	85319201

0/100 bar	direct	RF100I D201	●	85320201
0/160 bar	direct	RF100I D201	●	85321201
0/250 bar	direct	RF100I D201	●	85322201
0/400 bar	direct	RF100I D201	●	85323201
0/600 bar	direct	RF100I D201	●	85324201
0/1000 bar	direct	RF100I D201	●	85325201

● in-stock items

● Non-stock items