



## combined thermometer/pressure gauge TM80

**Part no. 63337**

**combined thermometer/pressure gauge**

### benefits

- pressure and temperature measurement with at a single measuring point
- with self-sealing connection thread for fast installation
- Bottom connection or back connection
- with mounting valve for easy replacement without downtime

### Application

For liquid media which are not highly viscous, do not crystallise and do not attack copper alloys. For combined measurement of pressure and temperature, especially in heating systems and heating boilers.

### Description

The combined thermometer/pressure gauge / thermo-hydrometer consists of a Bourdon tube measuring system for pressure measurement and a bimetal measuring system for simultaneous temperature measurement. Both values are measured and displayed by a single gauge. A self-closing mounting valve enable easy replacement of the measuring instrument without requiring the system to be drained. An optional M18 x 1 to G $\frac{1}{4}$  adapter is available if the combined thermometer/pressure gauge has to be mounted into an existing thermowell with M18 x 1 female thread.

### Technical Specifications

#### Type

D2

#### Nominal size

80

#### accuracy class

Pressure gauges: 2.5 (EN 837-1/6)

#### Range

pressure: 0/4 bar

temperature: 20/120 °C

#### application area

static load:  $\frac{3}{4}$  x full scale value

dynamic load:  $\frac{2}{3}$  x full scale value

short-term: Full scale value

temperature: Full scale value

#### Operating temperature range

Medium: max. 120 °C

Ambient: -20/+60 °C

#### Temperature performance

pressure: Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:

at rising temperature approx.  $\pm 0.4$  %/10 K

falling temperature approx.  $\pm 0.4$  %/10 K

of full scale value

### Degree of protection

IP 32 (EN 60529)

### Connection

Brass, bottom

G $\frac{1}{4}$ B with mounting valve G $\frac{1}{4}$  to R $\frac{1}{2}$

### Measuring element

pressure: Bourdon tube, Copper alloy

temperature: Bimetal spiral

### Dial

Plastic, white

Scaling: black with red/blue circular arcs

### Options

- Adapter M 18 x 1 to G $\frac{1}{4}$
- special scales
- other process connections

### Pointer

pressure: Plastic, black

temperature: Plastic, Red

### Housing

D2


Sheet steel, black

### window

Plastic, clipped in with adjustable red mark

## Technical Drawings

### Mounting valve and adapter



### Dimensions (mm)

pipe thread  
O ring (NBR)

Versions

| housing ø | Housing               | mounting position | Adapter | Range    |                  | Type         | Part no.                                                                            |       |
|-----------|-----------------------|-------------------|---------|----------|------------------|--------------|-------------------------------------------------------------------------------------|-------|
|           |                       |                   |         | pressure | temperatu-<br>re |              |                                                                                     |       |
| 80 mm     | Sheet<br>steel, black | bottom            |         | 0/4 bar  | 20/120 °C        | TM80<br>D201 |  | 63337 |

-  in-stock items
-  Non-stock items