



Leak detector control unit

benefits

- EU type examination certificate
- Version as per German WHG/AwSV and BetrSichV
- with fail-safe mode
- for monitoring of aboveground, double-walled tanks

Application

For double-walled tanks with liquid in the interstitial space. For monitoring water-polluting liquids with a flash point of $> 55^{\circ}\text{C}$ stored aboveground. Approved for all suitable tanks under atmospheric conditions.

Since July 2003, the LAG-13 KR leak detector may only be used for replacements of existing systems at underground, double-walled tanks as a result of the reclassification of water-polluting liquids in Germany!

Description

Leak detector class II (EN 13160-1/-3). The system consists of a control unit, a container for leak detection fluid (LAG container white) and a probe. Control unit with operating and alarm indicators, audible/visual alarm, test button and increased interference protection. The audible alarm can be muted with the Acknowledge button. The voltage-free relay contact is provided for connection of additional external alarm equipment (such as horns,) or an additional alarm unit ZAG 01. With fail-safe mode: Audible alarm if the probe fails. Suitable for panel mounting with a mounting frame; a sealing kit (IP 54) is available for rough application conditions. The LAG container serves as detection container and as expansion vessel at the same time. For aboveground tanks, the ratio between usable contents and total volume of leak detection fluid must be no more than 1:35. If the interstitial space has a greater volume, you must use additional containers.

Technical Specifications

Operating temperature range

Ambient: $-5/+50^{\circ}\text{C}$
Storage: $-10/+60^{\circ}\text{C}$

Supply voltage

AC 230 V

Nominal power

5 VA

Housing

Wall mounting housing made of impact-resistant plastic (ABS)
W x H x D: 100 x 188 x 65 mm
Weight: 400 g
Degree of protection: IP 30 (EN 60529)

Switching output

Relay contact: 1 x voltage-free changeover contact
Contact rating: AC 250 V, 2 A

Alarm sound

min. 70 dB(A)

approval

CE marking as per EC Construction Products Regulation 305/2011,
EU 574/2014, EN 13160-1/-3 and ÜHP

Scope of delivery

- Control unit

Versions

		Part no.
Control unit LAG-13 KR		40630
 in-stock items		
 Non-stock items		