

Diaphragm seal MD 22

Part no. 31999W

Diaphragm seals compact version



benefits

- robust, compact stainless steel design
- ideal for heavy fuel oil, suspensions and corrosive media
- suitable for medium pressure ranges

Application

For mounting to Bourdon tube pressure gauges, pressure transducers or pressure switches. For corrosive, hot and polluted media at medium pressures. Specially suitable for mechanical engineering and chemical industry applications.

Technical Specifications

Process connection

Stainless steel 316 L
fixed male thread ½-14 NPT

diaphragm

stainless steel 316 Ti/316 L
Internal, welded

Instrument connection

Welded connection

pressure transmission liquid

Paraffin oil (FM 09), FDA-listed

pressure range

see overview of versions

Nominal pressure


PN 40

Options

- Adapter for instrument connection G¼B/G½B
- Cooling element (> 100 °C)
- Capillary tube
- other threads
- other materials
- other filling liquids

Technical Drawings

Type MD 22



PN	G	ØA	ØD	h	H
40	G¼B	55	6	13	44,5
40	G¾B	55	6	16	47,5
40	G½B	55	10	20	51,5
40	¼"NPT	55	6	15	46,5
40	½"NPT	55	10	20	51,5
250	G¼B	40	6	13	44,5
250	G¾B	40	6	16	47,5
250	G½B	40	10	20	51,5
250	¼"NPT	40	6	15	46,5
250	½"NPT	40	10	20	51,5

Versions

Process connection	standard	Instru-ment con-nection	Nominal pressure	minimum range* (in bar) at nominal size					Part no.
				63	100	160	DMU	DMU 13 Vario	
½-14 NPT		Welded connection	PN 40	0.6 bar	0.6 bar	0.6 bar	0.6 bar	0.6 bar	31999W

- in-stock items
- Non-stock items