



Single line filters V 500 Si

Part no. 20292

Single-line filters for fuel oil

benefits

- with shut-off valve
- impact-resistant, shock-resistant and transparent plastic filter cup
- pipe connection via universal screw connection for pipes with Ø 8/10 mm
- materials resistant to biofuel and biodiesel mixtures with max. 30 % FA-ME
- Proofed Barrier (odour-tight)
- watertight up to 10 m water column - ideal for use in flood hazard areas

Application

For single-line systems with return line (version R 500) or without return line (version V 500). Suitable for fuel oil EL (DIN 51603-1), diesel fuel (EN 590), liquid fuels as per DIN SPEC 51603-6 and DIN/TS 51603-8 as well as biofuel and biodiesel with a maximum of 30 % FAME (EN 14214). This product is therefore ideal for all ecologically upgraded fuel oil consuming systems that use the new paraffinic fuels HVO or GTL as an admixture or 100 %. Also for use in flood hazard areas and flood risk areas.

Description

Brass filter housing, filter cup made of transparent, impact-resistant plastic. With shut-off valve in the flow line. Version R 500 also features a vent valve with hose connector in the return line. Universal compression fittings for pipes with 8/10 mm outside diameters included. Watertight up to 10 m water column.

Technical Specifications

connection burner end
see ordering table

Connection tank
see ordering table

Mounting position
filter cup vertically down

Operating temperature range
Medium: max. 40 °C

Operating overpressure
(suction mode only)

Material
Housing: Brass
Filter cup: Plastic, transparent and impact-resistant

approval
Conformity certificate (ÜHP) as per EN 12514

Versions

		Connection		Filter	oil throughput at Δp=100 m- bar		Part no.
		Tank	Burner				
Single line fil- ters V 500 Si	50–70 μm	1x G¾ female	1x G¾ male	sintered plas- tic sieve short, 50–70 μm	250 l/h		20292

-  in-stock items
-  Non-stock items