

Gas sensor GS 4.1 Propane/butane

Part no. 61189

Gas sensor

benefits

- additional sensor suitable for gas alarm unit GS 2.1
- detectable gases: methane or propane / butane
- LEDs indicate the operating and alarm state of the gas alarm system



Application

Additional gas sensor to be used with the gas alarm unit GS 2.1. Enables monitoring at two points in different rooms.

Description

Remote probe for gas alarm unit GS 2.1. Audible alarm is triggered by the gas alarm GS 2.1.

Detectable gases: Methane, butane, propane. LEDs at the sensor indicate the operating and alarm state of the gas alarm system:

LED green: operation

LED yellow: error

LED red: gas alarm

Technical Specifications

Supply voltage

via GS 2.1

Housing

Wall mounting plastic housing

W x H x D: 80 x 80 x 35 mm

Weight: ca. 500 g

Degree of protection: IP 20 (EN 60529)

Operating temperature range

Ambient: 0/50 °C

Storage: -10/+60 °C

Humidity/moisture: max. 75 % rH

Alarm value

ca. 20 % UEG

Service life

ca. 5 Jahre

Versions

	Part no.
Gas sensor GS 4.1 Propane/butane	61189

- ☒ in-stock items
- ☐ Non-stock items