



bimetal standard thermometer BiTh 100 K

Part no. 63677

Bimetal thermometer with brass thermowell

benefits

- ranges: -20/+60, 0/60, 0/120, 0/160 °C
- thermowell brass with optional self-sealing thread with PTFE sealing ring
- stem brass or aluminium

Application

Heating, plumbing

Technical Specifications

Nominal size
100

measuring element
Bimetal helix

accuracy class
2 (EN 13190)

standard version

Connection
Stem: brass or aluminium, Ø 9 mm
Thermowell: G1/2B, Brass, Ø 12 mm, removable

mounting position
centre back

Dial
Plastic, white
Scaling: black

Options

- nominal size 63 (bottom back)

ranges °C
-20/+60

application area
Full scale value

Operating pressure at thermowell
max. 6 bar


Pointer
Plastic, black

Housing
ABS, black

window
Plastic, clipped in

Technical Drawings

Centre back connection, NG 63 – 80 – 100



Dimensions (mm)

NG	B	D	d1	G	L1	L2	SW
63	14,7	62	12	G½B	40	61	19
63	14,7	62	12	G½B	63	85	19
63	14,7	62	12	G½B	100	122	19
63	14,7	62	12	G½B	150	172	19
80	14,8	79	12	G½B	40	61	19
80	14,8	79	12	G½B	63	85	19
80	14,8	79	12	G½B	100	122	19
80	14,8	79	12	G½B	150	172	19
100	15	100	12	G½B	40	61	19
100	15	100	12	G½B	63	85	19
100	15	100	12	G½B	100	122	19
100	15	100	12	G½B	150	172	19
100	15	100	12	G½B	200	222	19

Versions

Type	housing ø	Conne- ction	mounting position	Range	Stem length	Stem length	Type	Part no.
BiTh 100 K	100 mm	Thermo- well	centre back	-20/+60 °C	63 mm		BiTh 100 K	63677

-  in-stock items
-  Non-stock items