



CO₂ measuring instrument CM 20

Part no. 79134

CO₂ measuring instrument

benefits

- Monitoring of room air quality
- compact design
- visual indication of concentration
- Desktop unit with USB-C connection
- with or without EnOcean® wireless technology
- EEP (EnOcean® Equipment Profile): A5-09-09

Application

For continuous monitoring of the carbon dioxide (CO₂) concentration in the ambient air. Application in rooms in which many persons work, study or live and where carbon dioxide levels may consequently be elevated due to breathing, or in rooms where a very high air quality is required (for example, bedrooms, children's rooms). High concentrations of carbon dioxide in the ambient air reduce the ability of persons to concentrate and perform. In addition, the concentration of aerosols increases with the CO₂ concentration and, therefore, the risk of respiratory infections. Ideal for educational institutions, training/meeting rooms, office areas and household.

Description

Portable CO₂ sensor with infrared technology in a plastic housing with USB-C interface for power supply. The CO₂ concentration in the room air is indicated directly at the device by a colour scale:

LED green: No ventilation required

LED yellow: Ventilation recommended

LED red: Ventilation required

When the device switches from green to yellow (approx. 1,000 ppm), a short signal tone sounds (<1 second) which is repeated every ten minutes. When the device switches from yellow to red (approx. 1,500 ppm), two short signal tones sound which are repeated every ten minutes. The signal tone can be disabled. The version CM 20E (with EnOcean® wireless module) sends the measured values to the AFRISOhome gateway for further processing and initiation of appropriate action. For example, it is possible to start a room ventilation system in order to reduce the CO₂ concentration. The current carbon dioxide concentration and the history (day, week, month) is also displayed by the app AFRISOhome. This data is the ideal basis for ensuring healthy indoor ambient air. The AFRISOhome gateway in conjunction with additional AFRISO smart home products with EnOcean® wireless technology allows the user to configure a whole range of fully customisable, extensible applications.

Technical Specifications

Measuring range

0/2000 ppm

Operating temperature range

Ambient: 0/40 °C

Storage: -20/+60 °C

Housing

plastic housing (PC/ABS)
Colour: white, similar to RAL 9003
W x H x D: 50 x 60 x 50 mm
Weight: 80 g
Degree of protection: IP 20 (EN 60529)

Supply voltage

USB charger with mains plug

visual indication

LED green: < 1,000 ppm CO₂
LED yellow: 1,000–1,500 ppm CO₂
LED red: > 1,500 ppm CO₂

Scope of delivery

- CO₂ measuring instrument
- power supply unit
- Operating instructions

Versions

Part no.		
CO ₂ measuring instrument CM 20		79134

-  in-stock items
-  Non-stock items