



## Bourdon tube safety pressure gauges RF100Si

**Part no. 85469402**

**Bourdon tube safety pressure gauge type D4**

### benefits

- Safety housing S3 as per EN 837-1/9.7.2
- measuring system fully welded to housing
- tightness-tested with helium
- DNV- and GOSSTANDART-certified
- Ex version (optional)

### Application

For corrosive gaseous and liquid media which are not highly viscous and do not crystallise; suitable for corrosive environments. This gauge is designed for applications as per EN 837-1/9.7.2.

### Technical Specifications

#### Type

D4

#### Nominal size

100

#### accuracy class

EN 837-1/6

NG 100

1.0

#### ranges (EN 837-1/5)

see ordering table

#### application area

≤ 600 bar: Full scale value

> 600 bar:  $\frac{3}{4}$  x full scale value

≤ 600 bar: 0.9 x full scale value

> 600 bar:  $\frac{2}{3}$  x full scale value

≤ 600 bar: 1.3 x full scale value

> 600 bar: Full scale value

#### Operating temperature range

Medium: max. 100 °C

Ambient: -20/+60 °C

#### Degree of protection

IP 54 (EN 60529)

### standard version

#### Connection

Stainless steel 316 L, bottom

#### Measuring element

Bourdon tube  
stainless steel 316 Ti/316 L  
≤ 60 bar: "C" type tube  
> 60 bar: helical tube  
tightness-tested with helium

#### movement

Stainless steel

#### Dial

Aluminium, white  
Scaling: black

#### Options

- Glycerine filling (bottom version type D8)
- 3-hole fixing, panel mounting bezel
- Ex version
- special scales
- other process connections

#### Pointer

Aluminium, black

#### Housing

Stainless steel 304, with solid baffle wall and blow-out (S3)

#### bayonet bezel

Stainless steel 304

#### window

Laminated safety glass

#### Technical Drawings

NG 100/160 – bottom connection



Dimensions (mm)

| NG  | a  | b  | Øc | c1 | c2 | G   | h   | SW |
|-----|----|----|----|----|----|-----|-----|----|
| 100 | 27 | 60 | 6  | 3  | 20 | G½B | 86  | 22 |
| 160 | 40 | 78 | 6  | 3  | 20 | G½B | 118 | 22 |

Versions

| Range    | Mounting type | Type            |                                                                                     | Part number |
|----------|---------------|-----------------|-------------------------------------------------------------------------------------|-------------|
| 0/60 bar | direct        | RF100Si<br>D402 |  | 85469402    |

-  in-stock items
-  Non-stock items