



## Bourdon tube pressure gauges Process Gauge RF130PG

**Part no. 87903102**

**Standard Bourdon tube pressure gauge type D1**

### benefits

- extremely robust pressure gauge for offshore and onshore applications
- glass-fibre reinforced safety housing with solid baffle wall and blow-out
- integrated pressure compensation diaphragm
- tightness-tested with helium
- GOSSTANDART-certified

### Application

For corrosive gaseous and liquid media which are not highly viscous and do not crystallise. Specially suitable for the oil and chemical industries.

### Technical Specifications

#### Type

D1

#### Nominal size

4.5

#### accuracy class (ASME B 40.100)

Grade 2A (correspond to an accuracy of 0.5 %)

#### ranges (EN 837-1/5)

see ordering table

#### application area

static load: Full scale value

dynamic load: 0.9 x full scale value

short-term: 1.3 x full scale value

#### Operating temperature range

Medium: max. 100 °C

Ambient: -40/+65 °C

#### Temperature performance

Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:

at rising temperature approx.  $\pm 0.4 \text{ } \%/10 \text{ K}$

falling temperature approx.  $\pm 0.4 \text{ } \%/10 \text{ K}$   
of full scale value

#### Degree of protection

IP 67 (EN 60529)

### standard version

**Connection**

Stainless steel 316 L  
D102  
bottom

**Measuring element**

Bourdon tube, stainless steel 316 Ti/316 L  
≤ 60 bar: "C" type tube  
> 60 bar: helical tube  
tightness-tested with helium

**movement**

Stainless steel

**Dial**

Aluminium, white  
Scaling: black

**Options**

- Glycerine filling (type D 6)
- Silicone oil filling (type D 6)
- Measuring system copper alloy (type 1x1)
- Measuring system Monel (type 1x3)
- laminated safety glass window
- Reference pointer
- Maximum pointer
- Electrical contacts
- special scales
- other process connections

**Pointer**

micro-adjustable pointer  
Brass, black

**Housing**

PP-GF20, black  
with solid baffle wall and blow-out,  
Integrated back flange


**Screw type bezel**

PP-GF20, black Internal

**window**

Plastic (PMMA)

Technical Drawings



Versions

| Range       | Mounting type | Type            | Part number |
|-------------|---------------|-----------------|-------------|
| -1/+1.5 bar | back flange   | RF130PG<br>D102 | 87903102    |

- ☒ in-stock items
- ☐ Non-stock items