




## Stainless steel diaphragm pressure gauges PF160FLO

Part no. 88931402

Stainless steel diaphragm pressure gauge type D4

### benefits

- robust and compact design
- various process connections possible
- flush mounted versions without transmission liquid
- wetted area without seals due to welding
- GOSSTANDART-certified

### Application

For corrosive gaseous and liquid media, also for use in corrosive environments. With open connection flange also suitable for viscous and polluted media; with hygienic connections specially suitable for pharmaceutical processes. For measuring gas or vapour, observe the table "Selection Criteria as per EN 837-2" (see appendix)!

### Technical Specifications

**Type**  
D4

**Nominal size**  
160

**accuracy class (EN 837-3/6)**  
1.6

**ranges (EN 837-3/5)**  
see ordering table

**application area**  
static load: Full scale value  
dynamic load: 0.9 x full scale value

**Overpressure safety**  
≤ 6 bar  
at least 5 x FS

**Operating temperature range**  
Medium: max. 100 °C  
Ambient: -20/+60 °C

**Temperature performance**  
Indication error when the temperature of the measuring system deviates from the normal temperature of 20 °C:  
at rising temperature approx. ± 0.8 %/10 K  
falling temperature approx. ± 0.8 %/10 K  
of full scale value

**Degree of protection**  
IP 54 (EN 60529)

**standard version**

**Connection**

stainless steel 316 Ti/316 L, bottom  
open connection flange

**lower measuring flange**

stainless steel 316 Ti/316 L

**upper measuring flange**

Stainless steel 316 L

**Measuring element**

diaphragm  
≤ 2.5 bar  
stainless steel 316 Ti/316 L

**movement**

Stainless steel

**Options**

- Glycerine filling ( $\geq 1$  bar)
- wetted parts with special coating
- clamp connection
- Varivent or BioControl connection
- flush mounted connection flanges as per EN
- open connection flanges as per EN/ANSI
- Electrical contacts ( $\geq 0/0.6$  bar)
- other connection threads

**Dial**

Aluminium, white  
Scaling: black

**Pointer**

Aluminium, black

**Housing**

Stainless steel 304, with blow-out

**bayonet bezel**


Stainless steel 304

**window**

Laminated safety glass

Technical Drawings

connection flange as per EN 1092-1/B 1/DN 25/PN 40 open, 0/100 mbar to 0/25 bar



Dimensions (mm)

| Dimensions (mm) |    |    |     |       |     |   |    |
|-----------------|----|----|-----|-------|-----|---|----|
| NG              | d1 | d2 | d3  | G1    | h3  | s | s1 |
| 100             | 68 | 85 | 115 | 4xM12 | 102 | 2 | 30 |
| 160             | 68 | 85 | 115 | 4xM12 | 133 | 2 | 30 |

Versions

| Range   | Mounting type | Type             | Part number |
|---------|---------------|------------------|-------------|
| 0/1 bar | direct        | PF160FLO<br>D402 | 88931402    |

-  in-stock items
-  Non-stock items