



Glycerine filled Bourdon tube pressure gauges RF50Gly

Part no. 85072641

Glycerine filled Bourdon tube pressure gauge type D6

benefits

- can be used in case of heavy vibrations and high, dynamic pressure loads
- longer service life due to less wear and corrosion protection of the measuring system
- No steaming up of the inside of the window in case of outdoor applications

Application

For gaseous and liquid media which are not highly viscous, do not crystallise and do not attack copper alloys. For measurements in areas with high vibration levels and high, dynamic pressure loads.

Technical Specifications

Type

D6

Nominal size

50

accuracy class (EN 837-1/6)

1.6

ranges (EN 837-1/5)

see ordering table

standard version

Connection

Brass, centre back

application area

static load: $\frac{1}{4}$ x full scale value

dynamic load: $\frac{2}{3}$ x full scale value

short-term: Full scale value

Operating temperature range

Medium: max. 60 °C

Ambient: -20/+60 °C

Degree of protection

IP 65 (EN 60529)

Measuring element

Bourdon tube, Copper alloy

≤ 60 bar: "C" type tube

> 60 bar: helical tube

movement

Brass

Dial

NG 50

Aluminium, white

Scaling: black

Pointer

NG 50

Aluminium, black

Housing

NG 50

Polyamide, black
with blow-out

crimped bezel

NG 50

Aluminium, black

window

NG 50

Plastic

filling liquid


glycerine (99.5 %)

Options

- Back flange (NG 63)
- clamp fixing (NG 50/63)
- 3-hole fixing, panel mounting bezel (NG 63)
- throttle screw
- special scales
- other process connections

Technical Drawings

Centre back connection, with clamp fixing



Dimensions (mm)

NG	b	Øc	c1	c2	D	G	g	m	n	s	SW
50	31,5	5	2	13	53	G $\frac{1}{4}$ B	54,5	82	73	5	14
63	32	5	2	13	68	G $\frac{1}{4}$ B	55	94	82	7	14

Versions

Range	Mounting type	Type		Part number
0/250 bar	clamp fixing	RF50Gly D641		85072641

-  in-stock items
-  Non-stock items