


Heating pump assembly

benefits

- pre-assembled, tightness-tested and heat-insulated assembly
- modular system with flow at left or right
- easy, fast mounting
- with high-efficiency pump class A
- eligible for heating optimization program (BAFA)



**Sorry, kein Bild
vorhanden**

Application

Heating pump assembly for use in non-mixed heating circuits, specially for storage tank charging. It connects the heating boiler and the pipe system.

Description

Complete, pre-assembled and tightness-tested heating pump assembly with all required functional components, form-fit insulation and wall mounting unit.

The pump line (flow/hot) consists of:

Combination valve with thermometer in the hand wheel (red mark, range 0/120 °C)

Ball valve below the pump

Pipe for length compensation with screw connection

System connection G1½ male (boiler), G1 female (heating circuit)

Suitable for pumps DN 25 with G1½ x 180 mm.

The return line consists of:

Combination valve with gravity brake, thermometer in the handle (blue mark, range 0/120 °C)

Pipe for length compensation (pump/mixer) with screw connection

System connection G1½ male (boiler), G1 female (heating circuit)

Technical Specifications

Axis distance

125 mm

system connections

Boiler: G1½ male

Heating circuit: G1 female

Operating temperature range

Medium: max. 110 °C

System pressure

max. 10 bar

Nominal size

DN 25

Flow coefficient Kvs

4.8 m³/h

Insulation

Polypropylene EPP

Dimensions

W x H x D: 250 x 475 x 152 mm

Options

- Mixer and actuator, can be retrofitted
- other circulation pumps

Options

- Mixer and actuator, can be retrofitted
- other circulation pumps

Versions

	opening temperature is reached	Pump		Part no.
Heating pump assembly PrimoTherm® 180-1 DN 25		Without circulation pump	●	77643
Heating pump assembly PrimoTherm® 180-1 DN 25 GP		Grundfos UPM3 HYBRID 25-70/180	●	77645
Heating pump assembly PrimoTherm® 180-1 DN 25 WP		Wilo Para RS 25–180/6	●	77507

- in-stock items
- Non-stock items