



Inner lining for storage of liquid fertiliser AHL, AdBlue®

benefits

- inner linings for standardised cylindrical tanks (EN/DIN), tanks made on site consisting of steel, glass-fibre reinforced plastic or asbestos cement
- tank protection package with leak detector and complete mounting accessories on request
- customised training seminars on installation of inner linings and leak detectors possible

Application

For liquid fertiliser AHL and urea solution 32.5 % AdBlue®. Enquire for other liquids.

Description

Plastic inner linings, blue, with Technical Approval of the German Institute for Civil Engineering (DIBt) for cylindrical standard tanks, rectangular tanks consisting of steel, glass fibre reinforced or asbestos cement manufactured on site. Made of PVC film WP6120, 0.8 mm thick.

When AdBlue® is stored, the surface temperature must not exceed 35 °C!

Technical Specifications

approval

DIBt: Z-65.30-483

Versions

Tank volume		Part no.
3000 l	●	43880.003
5000 l	●	43880.005
7000 l	●	43880.007
10000 l	●	43880.010
13000 l	●	43880.013
15000 l	●	43880.015
16000 l	●	43880.016
20000 l	●	43880.020
25000 l	●	43880.025
30000 l	●	43880.030
40000 l	●	43880.040
50000 l	●	43880.050
60000 l	●	43880.060
80000 l	●	43880.080
100000 l	●	43880.100

● in-stock items

● Non-stock items