



Multi-channel process display

benefits

- Up to 90 channels for inputs/outputs
- 35 mathematical/logical functions
- 8 integrated PID controllers with autotuning
- 8 time-controlled/event-controlled profiles
- Touchscreen operation and remote operation
- Multi-level password system
- Web server with HTML5 widgets
- E-mail function

Application

Universal application for displaying and logging up to 16 independent analogue input signals, 8 binary inputs, 4 resistance thermometer inputs (RTD), 4 thermocouple inputs (TC) with freely selectable scaling and units. MPA 20 is very well suited for applications in which several physical measured variables reflect the state of an object and the state is controlled by several parameters at the same time.

Description

Digital display unit with integrated data logger in plastic housing for control panel mounting which allows for simultaneous measurement, visualisation and controlling of multiple channels. MPA 20 can operate autonomously or in conjunction with external measuring equipment and actuators. The multi-channel process display is designed as a modular device that consists of a base unit and optional input modules and output modules. The base unit comprises the main processor, a touch display, a switched-mode power supply (two available versions: 19–35 VDC and 85–260 VAC) as well as the communication interfaces (USB and RS 485).

Technical Specifications

Display

TFT touchscreen display 5.7"

User interface languages: German, English, French

Indication of value, bar chart, diagram, pointer, groups

Measuring range

Current inputs 0–20 mA

Voltage inputs 0–5 V, 1–5 V, 0–10 V, 2–10 V

Resistance thermometers

Thermocouple

Operating temperature range

Ambient: 0/50 °C

Supply voltage

AC/DC 85 – 260 V

Input resistance

Current: < 65 Ohm

voltage: > 100 kOhm

Housing

Panel housing

W x H x D: 144 x 144 x 110 mm

Weight

0.35 kg

Degree of protection

Housing, connection terminals: IP 20 (EN 60529)

Electrical connection

Plug-in screw terminals (1.5 mm²)

Interfaces

RS 485 (Modbus RTU)

RS 232

USB host

Ethernet (Modbus TCP)

Data memory

Internal memory 1.5 GB, max. 125,000,000 values

Acquisition of measured values of up to 60 channels

2 selectable measurement frequencies (max. 10 Hz)

comprehensive trigger functions

Data transmission via USB flash drive or Ethernet

Options

- Software
- DIN rail adapter

Slot P

02

Supply AC/DC 85–260 V

Output DC 24 V 200 mA

Digital input DC 24 V, RS-485 Modbus RTU

Special version

02

USB host port front

Options

- Software
- DIN rail adapter

Versions

			Slot D	Slot C/B/A		Part no.
	Supply AC/ DC 85–260 V	Special version USB host port front	empty	24 x current input (I)	●	MPA 20 02010102
	Supply AC/ DC 85–260 V	Special version USB host port front	empty	16 x binary input (D)	●	MPA 20 02010202
	Supply AC/ DC 85–260 V	Special version USB host port front	empty	4 x resistance thermometer input (RTD)	●	MPA 20 02010302
	Supply AC/ DC 85–260 V	Special version USB host port front	empty	4 x thermocouple input (TC)	●	MPA 20 02010402
	Supply AC/ DC 85–260 V	Special version USB host port front	empty	3 x universal input (I, U, RTD, TC)	●	MPA 20 02010502
	Supply AC/ DC 85–260 V	Special version USB host port front	empty	4 x current output	●	MPA 20 02010602
	Supply AC/ DC 85–260 V	Special version USB host port front	empty	12 x SPST relay 1A	●	MPA 20 02010702
	Supply AC/ DC 85–260 V	Special version USB host port front	USB host port rear	24 x current input (I)	●	MPA 20 02020102
	Supply AC/ DC 85–260 V	Special version USB host port front	USB host port rear	16 x binary input (D)	●	MPA 20 02020202
	Supply AC/ DC 85–260 V	Special version USB host port front	USB host port rear	4 x resistance thermometer input (RTD)	●	MPA 20 02020302
	Supply AC/ DC 85–260 V	Special version USB host port front	USB host port rear	4 x thermocouple input (TC)	●	MPA 20 02020402
	Supply AC/ DC 85–260 V	Special version USB host port front	USB host port rear	3 x universal input (I, U, RTD, TC)	●	MPA 20 02020502
	Supply AC/ DC 85–260 V	Special version USB host port front	USB host port rear	4 x current output	●	MPA 20 02020602

Supply AC/ DC 85–260 V	Special version USB host port front	USB host port re- ar	12 x SPST relay 1A	●	MPA 20 02020702
Supply AC/ DC 85–260 V	Special version USB host port front	USB host port re- ar Ethernet 10 Mbit/ s	24 x current inpu- t (I)	●	MPA 20 02030102
Supply AC/ DC 85–260 V	Special version USB host port front	USB host port re- ar Ethernet 10 Mbit/ s	16 x binary inpu- t (D)	●	MPA 20 02030202
Supply AC/ DC 85–260 V	Special version USB host port front	USB host port re- ar Ethernet 10 Mbit/ s	4 x resistance thermometer in- put (RTD)	●	MPA 20 02030302
Supply AC/ DC 85–260 V	Special version USB host port front	USB host port re- ar Ethernet 10 Mbit/ s	4 x thermocouple input (TC)	●	MPA 20 02030402
Supply AC/ DC 85–260 V	Special version USB host port front	USB host port re- ar Ethernet 10 Mbit/ s	3 x universal in- put (I, U, RTD, TC)	●	MPA 20 02030502
Supply AC/ DC 85–260 V	Special version USB host port front	USB host port re- ar Ethernet 10 Mbit/ s	4 x current output	●	MPA 20 02030602
Supply AC/ DC 85–260 V	Special version USB host port front	USB host port re- ar Ethernet 10 Mbit/ s	12 x SPST relay 1A	●	MPA 20 02030702

● in-stock items

● Non-stock items