



Pressure transducer industrial version

benefits

- DMU 04 CP/MR for hygienic processes
- small temperature error
- Options: Ex, field housing or high temperature version (up to 300 °C) and SIL 2

Application

For applications requiring hygienic process connections, materials or processing, especially food technology, pharmaceutical and biotechnology applications.

Description

Pressure transducers convert physical pressure into an electrical signal proportional to the pressure. DMU 4 is equipped with an oil-filled piezo-resistive silicon measuring cell. DMU 04 has safety integrity level SIL 2 (IEC 61508/61511).

Technical Specifications

Measuring accuracy

Deviation from the characteristic curve according to IEC 60770 – limit point calibration (non-linearity, hysteresis, repeatability)

Measuring range

see ordering table

Operating temperature range

Medium: -10/+125 °C

Medium: short-term (60 min) up to 150 °C

Ambient: -40/+85 °C

Storage: -40/+100 °C

dynamic characteristics

Response time: ≤ 10 ms

Process connection

G $\frac{1}{2}$ B DIN 3852 type E with flush diaphragm

material

Housing: Stainless steel 316 L

pressure connection: Stainless steel 316 L

diaphragm: Stainless steel 316 L

pressure transmission liquid

Food oil, FDA-compliant

Supply voltage

DC 8 – 32 V

Output signal

2-wire, 4–20 mA

Load

$$R_{\max} = [(UB - UB_{\min})/0.02 \text{ A}] \Omega$$

Current input

< 25 mA

electrical protection

short circuit proof and protected against reverse polarity

Electrical connection

Connector and junction box as per ISO 4400 (DIN 43650-A)

Degree of protection

IP 65 (EN 60529)

CE conformity

EMC Directive 2014/30/EU

RoHS Directive 2011/65/EU

Pressure Equipment Directive 2014/68/EU

Options

- other process connections
- other electrical connections
- Field housing (stainless steel 303)
- High temperature version up to 300 °C
- higher accuracy
- Union nut DN 25/40/50
- EX version (II 1G Ex ia IIC T4 Ga, II 1D Ex ia IIIC T85°C Da)
- SIL 2 (IEC 61508/61511) 2-wire

Versions

Range	Measuring range	Type	Version	Part no.
	-1/+1.5 bar	DMU 04		31647
	-1/+3 bar	DMU 04		31648
	-1/+5 bar	DMU 04		31649
	0/600 mbar	DMU 04		33018
	0/1 bar	DMU 04		33019
	0/1.6 bar	DMU 04		33020
	0/2.5 bar	DMU 04		31651
	0/4 bar	DMU 04		31652
	0/6 bar	DMU 04		31653
	0/10 bar	DMU 04		31654
	0/16 bar	DMU 04		31655
	0/25 bar	DMU 04		31656
	0/40 bar	DMU 04		31657
	0/60 bar	DMU 04		31658
	0/100 bar	DMU 04		31659
	0/160 bar	DMU 04		31660
	0/250 bar	DMU 04		31661
	0/400 bar	DMU 04		31662

-  in-stock items
-  Non-stock items